



Application:

Active Solution for Embedded Form Factor (MiniATX, EmbATX Board)

Specification:

Application System	Embedded Form Factor (MiniATX, EmbATX Board)
CPU Type	Intel Pentium M / Celeron M (Banias / Dothan / Sossaman / Yonah)
Supported CPU Frequency	All Frequency; FSB 400/533 MHz
Socket Type	478 Pins (Micro-FCPGA)
Heat Sink	Copper Base + Copper Stacked Fin
Cooler Dimension	50 x 50 x 45 mm
Fastener	Screw + Spring
Interface Material	Power Devices (Powerstrate ALS100-25-25-1S-BK)
Fan Dimension	40 x 40 x 10 mm
Fan Speed	5,500 RPM
Fan Airflow	5.3 CFM
Fan Bearing Type	Dual Ball Bearing
Voltage Rating	12 V
Noise Level	25 dBA
Connector	3 Pins
Mass	158 g
Quantity per carton	48 pcs
Thermal Resistance	Supported T1a = 67 °C for Banias FSB 400 MHZ Supported T1a = 72 °C for Dothan FSB 400 MHZ Supported T1a = 64 °C for Dothan FSB 533 MHZ
Backplate	BP (Inside)

Cooler Master Co., Ltd.

9F, No. 786, Chung-Cheng Rd., Chung-Ho City, Taipei Hsien, 235 Taiwan, R.O.C.

Tel: +886 (0)2 32340050

E-mail: ecd-pm@coolermaster.com

Fax: +886 (0)2 32340051

Web: <http://ecd.coolermaster.com>