

MI985

Intel® 5th Generation Core / QM87 PCH
Mini ITX Motherboard

USER'S MANUAL

Version 1.0

Acknowledgments

AMI is a registered trademark of American Megatrends Inc.
PS/2 is a trademark of International Business Machines Corporation.

Intel and Intel® 5th Generation Core DC/QC Processor are registered trademarks of Intel Corporation.

Microsoft Windows is a registered trademark of Microsoft Corporation.

Fintek is a registered trademark of Fintek Electronics Corporation.

All other product names or trademarks are properties of their respective owners.

Table of Contents

Introduction	1
Product Description.....	1
Checklist.....	1
MI985 Specifications	2
Board Dimensions	4
Installations	5
Installing the Memory.....	6
Setting the Jumpers.....	7
Connectors on MI985.....	12
BIOS Setup	25
Drivers Installation	48
Intel Chipset Software Installation Utility.....	49
VGA Drivers Installation.....	51
Realtek HD Audio Driver Installation	54
LAN Drivers Installation	56
Intel® Management Engine Interface	59
Intel® USB 3.0 Drivers.....	62
Appendix	65
A. I/O Port Address Map.....	65
B. Interrupt Request Lines (IRQ).....	66
C. Watchdog Timer Configuration	67

This page is intentionally left blank.

Introduction

Product Description

The MI985 Mini ITX motherboard is based on the latest Intel® QM87 chipset. The platform supports 5th generation Intel® Core processor family and features an integrated dual-channel DDR3L memory controller as well as a graphics core.

The latest Intel® processors provide advanced performance in both computing and graphics quality. This meets the requirement of customers in the gaming, POS, digital signage and server market segment.

The QM87 platform is made with 22-nanometer technology that supports Intel's first processor architecture to unite the CPU and the graphics core on the transistor level. The MI985 Mini ITX board utilizes the dramatic increase in performance provided this Intel's latest cutting-edge technology. Measuring 170mm x 170mm, the MI985 offers fast 6Gbps SATA support, USB3.0 and interfaces for DVI-D, DVI-I, LVDS and DP displays.

Checklist

Your MI985 package should include the items listed below.


- The MI985 Mini ITX motherboard
- This User's Manual
- 1 CD containing chipset drivers and flash memory utility
- Serial ATA cable
- IO shield

MI985 Specifications

Product Name	MI985AF [Support iAMT] **MI985AF is default model name on PCB**
Form Factor	Mini-ITX
CPU Type	Intel® 5 th Gen. Core™ mobile processors (14nm monolithic) FCBGA1364 , TDP = 47W (QC) Package size = 37.5 mmx 32 mm x 1.84mm
CPU Speed	1.6GHz ~ 2.0GHz
Cache	Up to 128MB
Chipset	Intel® DH82QM87 PCH Package size =20 mm x 20 mm x 1.573mm, TDP = 2.7W
BIOS	AMI BIOS
Memory	Intel® 5 th Gen. Core™ mobile processors integrated memory controller Supports dual channel DDR3L-1333/1600@1.35V SO-DIMM socket x 2 (Non-ECC type, unbuffered) Maximum capacity = 16GB
VGA	Intel® 5 th Gen. Core™ mobile processor integrated GPU (GT3e or GT2) Supports 3 independent displays: <ul style="list-style-type: none"> ● DVI-I X 1 (Thru port B, via VGA@ PCH+ Level shifter ASM1442K) ● DVI-D x 1 (Thru port C, with level shifter ASM1442K) ● DisplayPort x 1 (Thru port D) ● LVDS(Thru eDP, via NXP PTN3460)
LAN	1. Intel® I218LM GbE PHY ** Package = 6mm x 6mm, QFN48** 2. Intel® I211AT as 2 nd GbE
USB	USB 2.0 host controller inside QM87 PCH, supports 8 ports <ul style="list-style-type: none"> - 2 ports in the rear panel - 4 ports via onboard pin header - 2 ports via MiniPCIe sockets USB 3.0 host controller inside QM87 PCH, supports 4 ports <ul style="list-style-type: none"> - 4 ports in the rear panel
Serial ATA	Intel® QM87 PCH built-in SATA controller, supports total 6 ports 4 x SATA (3.0) 6Gbps & shared mSATA for 1 port (SATA port #5) 2 x SATA (2.0) 3Gbps
Audio	Intel® QM87 PCH built-in High Definition Audio controller + Realtek ALC892 w/ 7.1 channels
LPC I/O	Fintek F81866AD-I (128-pin LQFP [14mm x 14 mm]) <ul style="list-style-type: none"> - COM #1 (RS232/422/485) supports ring-in with power @500 mA (selectable for 5V or 12V) [EXAR SP339EER1 232/422/485 transceiver x 1 for jumperless] - COM #2 (RS232 only), supports ring-in with power @500 mA (selectable for 5V or 12V) - COM #3~COM #6 (RS232 only) Hardware Monitor (2 thermal inputs, 4 voltage monitor inputs & 2 fan headers) <ul style="list-style-type: none"> - CPU FAN x 1(PWn fan type, 4-pin connector) - SYS FAN x 1(PWM fan type, 4-pin connector)
Digital IO	4 in & 4 out
TPM 2.0	Infineon SLB9665 [C01Z9665TT2007000P] (MI985AFT only)
iAMT	Intel® Active Management Technology ver.10.0
Expansion Slots	- PCI-Express (16x) x1 [Gen 3.0 PEG] - Mini PCI-Express x 2 port [Full-sized] , both support USB 2.0 - One slot support mSATA (6Gbps)

Edge Connectors	Dual DB9 stack connector for COM #1 / #2 DVI-D + DVI-I stack connector x 1 DisplayPort + dual USB (2.0) stack connector x 1 RJ-45 + dual USB (3.0) stack connector x 2 Triplet type jack 3 x 1 for HD Audio
Onboard Header/Connector	4 ports x SATA III [Blue color] (One port shared with mSATA) 2 ports x SATA II DF-11 8-pin connector x 2 for 4 ports USB 2.0 DF-20 20-pin connector x 2 for dual -channel LVDS eDP LVDS panel connector x 1 2x5 pin-header x 1 for front panel audio [Supports 7.1 Channel] DF-11 10-pin pin-header x 4 for COM3 ~ COM6 2x5 pin-header x 1 for Digital IO 4-pin box header x 1 for LCD backlight control (thru iSMART)
Watchdog Timer	Yes (256 segments, 0, 1, 2...255 sec/min)
System Voltage	ATX standard 20-pin type 4 pin type (+12V only)[For full system loading usage]
Others	- iSMART 3.1 - Onboard CPU cooler (New Z-height from CPU)
Board Size	170mm x 170mm
Operation System	Windows 7, Windows8, Linux
Certification	CE /FCC/LVD

Board Dimensions



Installations

This section provides information on how to use the jumpers and connectors on the MI985 in order to set up a workable system. The topics covered are:

Installing the Memory	6
Setting the Jumpers.....	7
Connectors on MI985	12


Installing the Memory

The MI985 board supports two DDR3L memory socket for a maximum total memory of 16GB in DDR3L SODIMM memory type.

Installing and Removing Memory Modules

To install the DDR3L modules, locate the memory slot on the board and perform the following steps:

1. Hold the DDR3L module so that the key of the DDR3L module aligned with that on the memory slot.
2. Gently push the DDR3L module in an upright position until the clips of the slot close to hold the DDR3L module in place when the DDR3L module touches the bottom of the slot.
3. To remove the DDR3L module, press the clips with both hands.




Setting the Jumpers

Jumpers are used on MI985 to select various settings and features according to your needs and applications. Contact your supplier if you have doubts about the best configuration for your needs. The following lists the connectors on MI985 and their respective functions.

Jumper Locations on MI985	8
JP1: COM2 RS232 RI/+5V/+12V Power Setting.....	9
JP2: COM1 RS232 RI/+5V/+12V Power Setting.....	9
J13: LCD Panel Power Selection.....	10
J16: Flash Descriptor Security Override (Factory use only)	10
J17: Clear CMOS Contents.....	11
J18: Clear ME Contents.....	11

Jumper Locations on MI985



Jumpers on MI985.....Page

JP1: COM2 RS232 RI/+5V/+12V Power Setting..... 9

JP2: COM1 RS232 RI/+5V/+12V Power Setting..... 9


J13: LCD Panel Power Selection 10

J16: Flash Descriptor Security Override (Factory use only) 10

J17: Clear CMOS Contents..... 11


J18: Clear ME Contents..... 11

JP1: COM2 RS232 RI/+5V/+12V Power Setting




JP1	Setting	Function
	Pin 1-3, Short/Closed	+12V
	Pin 3-4, Short/Closed	RI
	Pin 3-5, Short/Closed	+5V

JP2: COM1 RS232 RI/+5V/+12V Power Setting




JP2	Setting	Function
	Pin 1-3, Short/Closed	+12V
	Pin 3-4, Short/Closed	RI
	Pin 3-5, Short/Closed	+5V

J13: LCD Panel Power Selection




J13	LCD Panel Power
 1 2 3	3.3V
 1 2 3	5V



J16: Flash Descriptor Security Override (Factory use only)




J16	Flash Descriptor Security Override
Open	Disabled (Default)
Close	Enabled



J17: Clear CMOS Contents



J17	Setting	Function
	Pin 1-2 Short/Closed	Normal
	Pin 2-3 Short/Closed	Clear CMOS

J18: Clear ME Contents





J18	Setting	Function
	Pin 1-2 Short/Closed	Normal
	Pin 2-3 Short/Closed	Clear CMOS

Connectors on MI985


Connector Locations on MI985	13
CN2: DVI-I and DVI-D Connector	14
CN1: COM1 and COM2 Serial Ports	15
CN4: Display Port	15
CN5: USB2 #6/#7	15
CN6: Gigabit LAN (I218) + USB3 #0/#1	15
CN7, CN8: SATA3 Connectors	15
CN9: Gigabit LAN (I218) + USB3 #2/#3	15
CN3: eDP Connector (JAE_FI-TD44SB-E-R750)	16
CN10: SATA2 Connector	17
CN11: SATA2 Connectors	17
CN12: HD Audio Connector	17
CN13: SATA3 Connector	17
CN14: SATA3 Connector	17
JP3, JP4: LVDS Connectors (LVDS2, LVDS1)	17
JP5: LCD Backlight Connector	18
JP6, JP8: USB2 #8/#9, USB2 #4/#5 Connectors	18
J1, J2, J3, J4: COM6, COM5, COM3, COM4 RS232 Serial Ports	19
J5: ATX Power Supply Connector	19
J6: ATX 12V Power Connector	20
JP7: LPC debug Connector (Factory use only)	20
JP9: SPI Flash Connector (Factory use only)	20
J7: PCIE1 Configuration	21
J8: Digital I/O Connector (4 in, 4 out)	21
J10, J11: DDR3L SO-DIMM Socket	21
J12: LVDS/eDP Select	22
J21: Audio Pin Header for Chassis Front Panel	22
J22: Front Panel	23
CPU_FAN1: CPU Fan Power Connector	23
SYS_FAN2: System Fan Power Connector (DC/PWM Auto-Detect)	24
J14: Mini PCIE/mSATA (share with CN7) Connector	24
J15: Mini PCIE Connector	24

Connector Locations on MI985







CN2: DVI-I and DVI-D Connector




Signal Name	Pin #	Pin #	Signal Name
DATA 2-	1	16	HOT POWER
DATA 2+	2	17	DATA 0-
Shield 2/4	3	18	DATA 0+
DATA 4-	4	19	SHIELD 0/5
DATA 4+	5	20	DATA 5-
DDC CLOCK	6	21	DATA 5+
DDC DATA	7	22	SHIELD CLK
Analog VSYNC	8	23	CLOCK -
DATA 1-	9	24	CLOCK +
DATA 1+	10	C1	Analog Red
SHIELD 1/3	11	C2	Analog Green
DATA 3-	12	C3	Analog Blue
DATA 3+	13	C4	Analog HSYNC
DDC POWER	14	C5	A GROUND2
A GROUND 1	15	C6	A GROUND3



Signal Name	Pin #	Pin #	Signal Name
DATA 2-	1	16	HOT POWER
DATA 2+	2	17	DATA 0-
Shield 2/4	3	18	DATA 0+
DATA 4-	4	19	SHIELD 0/5
DATA 4+	5	20	DATA 5-
DDC CLOCK	6	21	DATA 5+
DDC DATA	7	22	SHIELD CLK
N.C	8	23	CLOCK -
DATA 1-	9	24	CLOCK +
DATA 1+	10	C1	N.C.
SHIELD 1/3	11	C2	N.C.
DATA 3-	12	C3	N.C.
DATA 3+	13	C4	N.C.
DDC POWER	14	C5	N.C.
A GROUND 1	15	C6	N.C.



CN1: COM1 and COM2 Serial Ports



Pin #	Signal Name		
	RS-232	R2-422	RS-485
1	DCD	TX-	DATA-
2	RX	TX+	DATA+
3	TX	RX+	NC
4	DTR	RX-	NC
5	Ground	Ground	Ground
6	DSR	NC	NC
7	RTS	NC	NC
8	CTS	NC	NC
9	RI	NC	NC
10	NC	NC	NC

CN4: Display Port

Signal Name	Pin #	Pin #	Signal Name
LANE0_P	1	11	GND
GND	2	12	LANE3_N
LANE0_N	3	13	GND
LANE1_P	4	14	GND
GND	5	15	AUX_P
LANE1_N	6	16	GND
LANE2_P	7	17	AUX_N
GND	8	18	HPD
LANE2_N	9	19	GND
LANE3_P	10	20	VCC3.


CN5: USB2 #6/#7

CN6: Gigabit LAN (I218) + USB3 #0/#1

CN7, CN8: SATA3 Connectors

CN9: Gigabit LAN (I211) + USB3 #2/#3

CN3: eDP Connector (JAE_FI-TD44SB-E-R750)



Signal Name	Pin #	Pin #	Signal Name
3.3V	1	23	TXN0
3.3V	2	24	TXP0
3.3V	3	25	GND
3.3V	4	26	AUXP
3.3V	5	27	AUXN
GND	6	28	NC
GND	7	29	VCC3
GND	8	30	NC
GND	9	31	VCC12
HPD	10	32	NC
NC	11	33	GND
NC	12	34	VCC5
GND	13	35	NC
NC	14	36	Brightness
NC	15	37	BKLT_EN
GND	16	38	VCC12
NC	17	39	VCC3
NC	18	40	GND
GND	19	41	SMB_THRM_CLK
TXN1	20	42	SMB_THRM_DATA
TXP1	21	43	NC
GND	22	44	NC

CN10: SATA2 Connector

CN11: SATA2 Connectors


CN12: HD Audio Connector

CN13: SATA3 Connector

CN14: SATA3 Connector


JP3, JP4: LVDS Connectors (LVDS2, LVDS1) Hirose DF20G-20DP-1V

The LVDS connectors on board consist of the first channel (LVDS1) and second channel (LVDS2).




Signal Name	Pin #	Pin #	Signal Name
TX0N	2	1	TX0P
Ground	4	3	Ground
TX1N	6	5	TX1P
Ground	8	7	Ground
TX2N	10	9	TX2P
Ground	12	11	Ground
CLKN	14	13	CLKP
Ground	16	15	Ground
TX3N	18	17	TX3P
Power	20	19	Power

JP5: LCD Backlight Connector




Pin #	Signal Name
1	+12V
2	Backlight Enable
3	Brightness Control
4	Ground

JP6, JP8: USB2 #8/#9, USB2 #4/#5 Connectors




Signal Name	Pin #	Pin #	Signal Name
Vcc	1	2	Ground
D0-	3	4	D1+
D0+	5	6	D1-
Ground	7	8	Vcc

J1, J2, J3, J4: COM6, COM5, COM3, COM4 RS232 Serial Ports (HIROSE DF11-10DP-2DSA)




Signal Name	Pin #	Pin #	Signal Name
DCD#	1	2	SIN#
SOUT	3	4	DTR#
GND	5	6	DSR#
RTS#	7	8	CTS#
RI#	9	X	KEY

J5: ATX Power Supply Connector



Signal Name	Pin #	Pin #	Signal Name
3.3V	11	1	3.3V
-12V	12	2	3.3V
Ground	13	3	Ground
PS-ON	14	4	+5V
Ground	15	5	Ground
Ground	16	6	+5V
Ground	17	7	Ground
-5V	18	8	Power good
+5V	19	9	5VSB
+5V	20	10	+12V

J6: ATX 12V Power Connector




This connector supplies the CPU operating voltage.

Pin #	Signal Name
1	Ground
2	Ground
3	+12V
4	+12V

JP7: LPC debug Connector (Factory use only)



JP9: SPI Flash Connector (Factory use only)

J7: PCIE1 Configuration



J7	PCIE1 Configuration
Open	PCIE X16 (Default)
Short	PCIE X8, X8


J8: Digital I/O Connector (4 in, 4 out)



Signal Name	Pin #	Pin #	Signal Name
Ground	1	2	+5V
Out3	3	4	Out1
Out2	5	6	Out0
IN3	7	8	IN1
IN2	9	10	IN0


J10, J11: DDR3L SO-DIMM Socket

J12: LVDS/eDP Select




J12	Setting	Function
	Pin 1-2, Short/Closed	eDP Connector
	Pin 2-3, Short/Closed	LVDS

J21: Audio Pin Header for Chassis Front Panel




Signal Name	Pin #	Pin #	Signal Name
MIC IN_L	1	2	Ground
MIC IN_R	3	4	DET
LINE_R	5	6	Ground
Sense	7	8	KEY
LINE_L	9	10	Ground

J22: Front Panel




Signal Name	Pin #	Pin #	Signal Name
Power BTN	1	2	Power BTN
HDD LED+	3	4	HDD LED-
Reset BTN	5	6	Reset BTN
Power LED+	7	8	Power LED-

CPU_FAN1: CPU Fan Power Connector



Pin #	Signal Name
1	Ground
2	+12V
3	Rotation detection
4	Control

SYS_FAN2: System Fan Power Connector (DC/PWM Auto-Detect)



Pin #	Signal Name
1	Ground
2	+12V
3	Rotation detection
4	Control

J14: Mini PCIE/mSATA (share with CN7) Connector

J15: Mini PCIE Connector

BIOS Setup

This chapter describes the different settings available in the AMI BIOS that comes with the board. The topics covered in this chapter are as follows:

BIOS Introduction.....	26
BIOS Setup.....	26
Advanced Settings	28
Chipset Settings	41
Security Settings	45
Boot Settings.....	46
Save & Exit Settings	47

BIOS Introduction

The BIOS (Basic Input/Output System) installed in your computer system's ROM supports Intel processors. The BIOS provides critical low-level support for a standard device such as disk drives, serial ports and parallel ports. It also provides password protection as well as special support for detailed fine-tuning of the chipset controlling the entire system.

BIOS Setup

The BIOS provides a Setup utility program for specifying the system configurations and settings. The BIOS ROM of the system stores the Setup utility. When you turn on the computer, the BIOS is immediately activated. Pressing the key immediately allows you to enter the Setup utility. If you are a little bit late pressing the key, POST (Power On Self Test) will continue with its test routines, thus preventing you from invoking the Setup. If you still wish to enter Setup, restart the system by pressing the "Reset" button or simultaneously pressing the <Ctrl>, <Alt> and <Delete> keys. You can also restart by turning the system Off and back On again. The following message will appear on the screen:

```
Press <DEL> to Enter Setup
```

In general, you press the arrow keys to highlight items, <Enter> to select, the <PgUp> and <PgDn> keys to change entries, <F1> for help and <Esc> to quit.

When you enter the Setup utility, the Main Menu screen will appear on the screen. The Main Menu allows you to select from various setup functions and exit choices.

Warning: *It is strongly recommended that you avoid making any changes to the chipset defaults. These defaults have been carefully chosen by both AMI and your system manufacturer to provide the absolute maximum performance and reliability. Changing the defaults could cause the system to become unstable and crash in some cases.*

Main Settings

Aptio Setup Utility – Copyright © 2013 American Megatrends, Inc.

Main	Advanced	Chipset	Boot	Security	Save & Exit
					Choose the system default language
Total Memory			8192 MB (DDR3)		→ ← Select Screen
Memory Frequency			1600 Mhz		↑ ↓ Select Item
System Date			[Mon 06/22/2015]		Enter: Select
System Time			[18:21:30]		+ - Change Field
Access Level			Administrator		F1: General Help
					F2: Previous Values
					F3: Optimized Default
					F4: Save ESC: Exit

System Date

Set the Date. Use Tab to switch between Data elements.

System Time

Set the Time. Use Tab to switch between Data elements.

Advanced Settings

This section allows you to configure and improve your system and allows you to set up some system features according to your preference.

Aptio Setup Utility

Main	Advanced	Chipset	Boot	Security	Save & Exit
	<ul style="list-style-type: none">▶ CPU Configuration▶ Trusted Computing▶ ACPI Settings▶ LVDS (eDP/DP) Configuration▶ iSmart Controller▶ AMT Configuration▶ F81866 Super IO Configuration▶ Hardware Monitor▶ SATA Configuration▶ CSM Configuration▶ USB Configuration				<p>→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit</p>

CPU Configuration

This section shows the CPU configuration parameters.

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
CPU Configuration					
Genuine Intel(R) CPU 0000 @ 2.00GHz					
CPU Signature			40671		
Microcode Patch			d		
Max CPU Speed			2000 MHz		
Min CPU Speed			800 MHz		
CPU Speed			2700 MHz		
Processor Cores			4		
Intel HT Technology			Supported		
Intel VT-x Technology			Supported		
Intel SMX Technology			Supported		
64-bit			Supported		
EIST Technology			Supported		
Hyper-threading			Enabled		
Active Processor Cores			All		
Overclocking lock			Disabled		
Execute Disable Bit			Enabled		
Intel Virtualization Technology			Enabled		
EIST			Enabled		
Turbo Mode			Enabled		
					→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit

Hyper-threading

Enabled for Windows XP and Linux (OS optimized for Hyper-Threading Technology) and Disabled for other OS (OS not optimized for Hyper-Threading Technology). When Disabled only one thread per enabled core is enabled.

Active Processor Cores

Number of cores to enable in each processor package.

Overclocking lock

FLEX_RATIO(194) MSR

Execute Disable Bit

XD can prevent certain classes of malicious buffer overflow attacks when combined with a supporting OS (Windows Server 2003 SP1, Windows XP SP2, SuSE Linux 9.2, RedHat Enterprise 3 Update 3.)

Intel Virtualization Technology

When enabled, a VMM can utilize the additional hardware capabilities provided by Vanderpool Technology.

EIST

Enabled/Disabled Intel Speedstep.

Turbo Mode

Turbo Mode.

Trusted Computing

Aptio Setup Utility – Copyright © 2012 American Megatrends, Inc.

Main	Advanced	Chipset	Boot	Security	Save & Exit
TPM20 Device Found					
Security Device Support			Enable		→ ← Select Screen
Pending operation			None		↑ ↓ Select Item
Platform Hierarchy			Enabled		Enter: Select
Storage Hierarchy			Enabled		+ - Change Opt.
Endorsement Hierarchy			Enabled		F1: General Help
HashPolicy			Sha-1		F2: Previous Values
TPM 20 InterfaceType			TIS		F3: Optimized Defaults
Device Select			Auto		F4: Save & Exit
					ESC: Exit

Security Device Support

Enables or Disables BIOS support for security device. O.S. will not show Security Device. TCG EFI protocol and INT1A interface will not be available.

Pending operation

Schedule an Operation for the Security Device. NOTE: Your Computer will reboot during restart in order to change State of Security Device.

Platform Hierarchy

Enable or Disable Platform Hierarchy

Storage Hierarchy

Enable or Disable Storage Hierarchy

Endorsement Hierarchy

Enable or Disable Endorsement Hierarchy

HashPolicy

Select the Hash policy to use. SHA-2 is most secure but might not be supported by all Operating Systems

TPM 20 InterfaceType

Select the Communication Interface to TPM 20 Device.

Device Select

TPM 1.2 will restrict support to TPM 1.2 devices, TPM 2.0 will restrict support to TPM 2.0 devices, Auto will support both with the default set to TPM 2.0 devices if not found, TPM 1.2 devices will be enumerated

ACPI Settings

Aptio Setup Utility

Main	Advanced	Chipset	Boot	Security	Save & Exit
ACPI Settings					
Enable Hibernation			Enabled		
ACPI Sleep State			S3 (Suspend to R...)		
Lock Legacy Resources			Disabled		
				→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit	

Enable Hibernation

Enables or Disables System ability to Hibernate (OS/S4 Sleep State). This option may be not effective with some OS.

ACPI Sleep State

Select ACPI sleep state the system will enter, when the *SUSPEND* button is pressed.

Lock Legacy Resources

Enabled or Disabled Lock of Legacy Resources.

LVDS (eDP/DP) Configuration

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
LVDS (eDP/DP) Configuration					
LVDS (eDP/DP) Support		Disable		→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit	

LVDS (eDP/DP) Support

LVDS (eDP/DP) ON/OFF

iSmart Controller

Aptio Setup Utility - Copyright © 2012 American Megatrends, Inc.

Aptio Setup Utility - Copyright © 2012 American Megatrends, Inc.					
Main	Advanced	Chipset	Boot	Security	Save & Exit
iSmart Controller					
Power-On after Power failure		Disable		→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit	
Temperature Guardian		Disable			
Schedule Slot 1		None			
Schedule Slot 2		None			

Power-On after Power failure

This field sets the system power status whether Disable or Enable when power returns to the system from a power failure situation.

Temperature Guardian

Generate the reset signal when system hangs up on POST.

Schedule Slot 1 / 2

Setup the hour/minute for system power on.

AMT Configuration

Aptio Setup Utility

Main	Advanced	Chipset	Boot	Security	Save & Exit
			Intel AMT	Enabled	
			BIOS Hotkey Pressed	Disabled	
			MEBx Selection Screen	Disabled	
			Hide Un-Configure ME Confirmation	Disabled	
			Amt Wait Timer	0	→ ← Select Screen
			Activate Remote Assistance Process	Disabled	↑ ↓ Select Item
			USB Configure	Enabled	Enter: Select
			PET Progress	Enabled	+ - Change Field
			AMT CIRA Timeout	0	F1: General Help
			Watchdog	Disabled	F2: Previous Values
			OS Timer	0	F3: Optimized Default
			BIOS Timer	0	F4: Save
					ESC: Exit

Intel AMT

Enable/Disable Intel (R) Active Management Technology BIOS Extension.

Note: iAMT H/W is always enabled. This option just controls the BIOS extension execution. If enabled, this requires additional firmware in the SPI device

BIOS Hotkey Pressed

OEMFLag Bit 1:

Enable/Disable BIOS hotkey press.

AMT Configuration

OEMFLag Bit 2:

Enable/Disable MEBx selection screen.

Hide Un-Configure ME Configuration

OEMFlag Bit 6:

Hide Un-Configure ME without password Confirmation Prompt

Amt Wait Timer

Set timer to wait before sending ASF_GET_BOOT_OPTIONS.

Activate Remote Assistance Process

Trigger CIRA boot.

USB Configure

Enable/Disable USB Configure function.

PET Progress

User can Enable/Disable PET Events progress to receive PET events or not.

Watchdog Timer

Enable/Disable Watchdog Timer.

F81866 Super IO Configuration

Aptio Setup Utility

Main	Advanced	Chipset	Boot	Security	Save & Exit
F81866 Super IO Configuration					
Super IO Chip		F81866			
▶ Serial Port 1 Configuration				→ ← Select Screen	
▶ Serial Port 2 Configuration				↑ ↓ Select Item	
▶ Serial Port 3 Configuration				Enter: Select	
▶ Serial Port 4 Configuration				+- Change Field	
▶ Serial Port 5 Configuration				F1: General Help	
▶ Serial Port 6 Configuration				F2: Previous Values	
				F3: Optimized Default	
				F4: Save	
				ESC: Exit	

Serial Port Configuration

Set parameters of serial ports. User can Enable/Disable the serial port and Select an optimal settings for the Super IO Device.

Hardware Monitor

Aptio Setup Utility

Main	Advanced	Chipset	Boot	Security	Save & Exit
PC Health Status					
CPU Smart Fan Control		Disabled			
CPU	Temperature	+35 C			→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit
System	Temperature	+35 C			
CPU	Fan Speed	6976 RPM			
VCCIN		+1.856 V			
VCC5V		+5.129 V			
VCC12V		+12.232 V			
VDD		+1.392 V			
VCC3V		+3.360 V			
VSB3V		+3.360 V			
VSB5V		+4.944 V			
CPU Shutdown Temperature		Disable			

CPU Smart Fan Control

The default setting is Disabled.

Temperatures/Voltages

These fields are the parameters of the hardware monitoring function feature of the board. The values are read-only values as monitored by the system and show the PC health status.

CPU Shutdown Temperature

The default setting is Disabled.

SATA Configuration

SATA Devices Configuration.

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
	SATA Controller(s)		Enabled		
	SATA Mode Selection		AHCI		
	Serial ATA Port 0		Empty		
	Software Preserve		Unknown		
	Port 0		Enabled		
	Serial ATA Port 1		Empty		
	Software Preserve		Unknown		
	Port 1		Enabled		→ ← Select Screen
	Serial ATA Port 2		Empty		↑ ↓ Select Item
	Software Preserve		Unknown		Enter: Select
	Port 2		Enabled		+ - Change Field
	Serial ATA Port 3		Empty		F1: General Help
	Software Preserve		Unknown		F2: Previous Values
	Port 3		Enabled		F3: Optimized Default
	Serial ATA Port 4		Empty		F4: Save
	Software Preserve		Unknown		ESC: Exit
	Port 4		Enabled		
	Serial ATA Port 5		Empty		
	Software Preserve		Unknown		
	Port 5		Enabled		

SATA Controller(s)

Enable / Disable Serial ATA Controller.

SATA Mode Selection

- (1) IDE Mode.
- (2) AHCI Mode.
- (3) RAID Mode.

Port

Enable or Disable SATA Port

CSM Configuration

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
Compatibility Support Module Configuration					
CSM Support			Enabled		
CSM16 Module Version			07.77		
GateA20 Active			Upon Request		
Option ROM Messages			Force BIOS		
Boot option filter			UEFI and Legacy		
Option ROM execution					
Network			Do not launch		
Storage			Legacy		
Video			Legacy		
Other PCI device			UEFI		
→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit					

CSM Support

Enable/Disable CSM Support.

Boot option filter

This option controls what devices system can boot to.

Network

Controls the execution of UEFI and Legacy PXE OpROM.

Storage

Controls the execution of UEFI and Legacy Storage OpROM.

Video

Controls the execution of UEFI and Legacy Video OpROM.

Other PCI device

Determines OpROM execution policy for devices other than Network, Storage, or Video.

USB Configuration

Aptio Setup Utility

Main	Advanced	Chipset	Boot	Security	Save & Exit
USB Configuration					
USB Module Version			11		
USB Controllers:					
2 EHCIs, 1 XHCI					
USB Devices:					
1 Drive, 1 Keyboard, 1 Mouse , 2 Hubs					
Legacy USB Support				Enabled	→ ← Select Screen
XHCI Hand-off				Enabled	↑ ↓ Select Item
EHCI Hand-off				Enabled	Enter: Select
USB Mass Storage Driver Support				Enabled	+ - Change Field
					F1: General Help
					F2: Previous Values
					F3: Optimized Default
USB hardware delays and time-outs:					F4: Save
USB Transfer time-out			20 sec		ESC: Exit
Device reset time-out			20 sec		
Device power-up delay			Auto		

Legacy USB Support

Enables Legacy USB support.

AUTO option disables legacy support if no USB devices are connected. DISABLE option keeps USB devices available only for EFI applications.

XHCI Hand-off

This is a workaround for Oses without XHCI hand-off support. The XHCI ownership change should be claimed by XHCI driver.

USB Mass Storage Driver Support

Enable/Disable USB Mass Storage Driver Support.

EHCI Hand-off

This is a workaround for Oses without EHCI hand-off support. The EHCI ownership change should be claimed by EHCI driver.

USB Transfer time-out

The time-out value for Control, Bulk, and Interrupt transfers.

Device reset time-out

USB mass Storage device start Unit command time-out.

Device power-up delay

Maximum time the device will take before it properly reports itself to the Host Controller. ‘Auto’ uses default value: for a Root port it is 100ms, for a Hub port the delay is taken from Hub descriptor.

Chipset Settings

This section allows you to configure and improve your system and allows you to set up some system features according to your preference.

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
<ul style="list-style-type: none"> ▶ System Agent (SA) Configuration ▶ PCH-IO Configuration 					

System Agent (SA) Configuration

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
System Agent Bridge Name		Broadwell			
System Agent RC Version		2.7.1.0			
VT-d Capability		Supported			
VT-d		Enabled		→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit	
▶ Graphics Configuration					

VT-d

Check to enable VT-d function on MCH.

PCH-IO Configuration

This section allows you to configure the North Bridge Chipset.

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
		Intel PCH RC Version	2.7.1.0		
		Intel PCH SKU Name	QM87		
		Intel PCH Rev ID	05/C2		
		▶ PCI Express Configuration			→ ← Select Screen
		▶ USB Configuration			↑ ↓ Select Item
		▶ PCH Azalia Configuration			Enter: Select
					+ - Change Field
					F1: General Help
		PCH LAN Controller	Enabled		F2: Previous Values
		Wake on LAN	Enabled		F3: Optimized Default
					F4: Save
					ESC: Exit

PCH LAN Controller

Enable or disable onboard NIC.

Wake on LAN

Enable or disable integrated LAN to wake the system. (The Wake On LAN cannot be disabled if ME is on at Sx state.)

PCI Express Configuration

Main	Advanced	Chipset	Boot	Security	Save & Exit
PCI Express Configuration <ul style="list-style-type: none"> ▶ PCI Express Root Port 1 ▶ PCI Express Root Port 2 ▶ PCI Express Root Port 3 ▶ PCI Express Root Port 4 ▶ PCI Express Root Port 5 <ul style="list-style-type: none"> PCI Port 6 is assigned to LAN ▶ PCI Express Root Port 7 ▶ PCI Express Root Port 8 					→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit

PCI Express Configuration

PCI Express Root Port Settings.

USB Configuration

Main	Advanced	Chipset	Boot	Security	Save & Exit
USB Configuration					→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit
USB Precondition		Disabled			
xHCI Mode		Auto			
USB Ports Per-Port Disable Control		Disabled			

USB Precondition

Precondition work on USB host controller and root ports for faster enumeration.

xHCI Mode

Mode of operation of xHCI controller.

USB Ports Per-Port Disable Control

Control each of the USB ports (0~13) disabling.

PCH Azalia Configuration

Main	Advanced	Chipset	Boot	Security	Save & Exit
PCH Azalia Configuration					→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit
Azalia		Enabled			

Azalia

Control Detection of the Azalia device.

Disabled = Azalia will be unconditionally be disabled.

Enabled = Azalia will be unconditionally be enabled.

Auto = Azalia will be enabled if present, disabled otherwise.

Security Settings

This section allows you to configure and improve your system and allows you to set up some system features according to your preference.

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
Password Description					
If ONLY the Administrator's password is set, then this only limit access to Setup and is only asked for when entering Setup.					
If ONLY the User's password is set, then this is a power on password and must be entered to boot or enter Setup. In Setup the User will have Administrator rights					
The password length must be in the following range:					
Minimum length			3		
Maximum length			20		
Administrator Password					
User Password					
		→ ← Select Screen ↑ ↓ Select Item Enter: Select +- Change Field F1: General Help F2: Previous Values F3: Optimized Default F4: Save ESC: Exit			

Administrator Password

Set Setup Administrator Password.

User Password

Set User Password.

Boot Settings

This section allows you to configure the boot settings.

Aptio Setup Utility					
Main	Advanced	Chipset	Boot	Security	Save & Exit
Boot Configuration					
Setup Prompt Timeout		1			
Bootup NumLock State		On			
Quiet Boot		Disabled			
Fast Boot		Disabled			
Boot mode select		LEGACY			
FIXED BOOT ORDER Priorities					
Boot Option #1		Hard Disk			→ ← Select Screen
Boot Option #2		CD / DVD			↑ ↓ Select Item
Boot Option #3		USB Hard Disk			Enter: Select
Boot Option #4		USB CD / DVD			+ - Change Field
Boot Option #5		USB Key			F1: General Help
Boot Option #6		USB Floppy			F2: Previous Values
Boot Option #7		USB LAN			F3: Optimized Default
Boot Option #8		Network			F4: Save
					ESC: Exit

Setup Prompt Timeout

Number of seconds to wait for setup activation key.
65535(0xFFFF) means indefinite waiting.

Bootup NumLock State

Select the keyboard NumLock state.

Quiet Boot

Enables/Disables Quiet Boot option.

Fast Boot

Enables/Disables boot with initialization of a minimal set of devices required to launch active boot option. Has no effect for BBS boot options.

Boot mode select

Select boot mode LEGACY/UEFI

Fixed Boot Order Priorities

Sets the system boot order.

Save & Exit Settings

Main	Advanced	Chipset	Boot	Security	Save & Exit
Save Changes and Exit					
Discard Changes and Exit					
Save Changes and Reset					
Discard Changes and Reset					
Save Options					→ ← Select Screen
Save Changes					↑ ↓ Select Item
Discard Changes					Enter: Select
					+ - Change Field
					F1: General Help
					F2: Previous Values
					F3: Optimized Default
					F4: Save
					ESC: Exit
Restore Defaults					
Save as User Defaults					
Restore User Defaults					
Boot Override					

Save Changes and Exit

Exit system setup after saving the changes.

Discard Changes and Exit

Exit system setup without saving any changes.

Save Changes and Reset

Reset the system after saving the changes.

Discard Changes and Reset

Reset system setup without saving any changes.

Save Changes

Save Changes done so far to any of the setup options.

Discard Changes

Discard Changes done so far to any of the setup options.

Restore Defaults

Restore/Load Defaults values for all the setup options.

Save as User Defaults

Save the changes done so far as User Defaults.

Restore User Defaults

Restore the User Defaults to all the setup options.

Drivers Installation

This section describes the installation procedures for software and drivers. The software and drivers are included with the motherboard. If you find the items missing, please contact the vendor where you made the purchase. The contents of this section include the following:

Intel Chipset Software Installation Utility.....	49
VGA Drivers Installation	51
Realtek HD Audio Driver Installation	54
LAN Drivers Installation.....	56
Intel® Management Engine Interface.....	59
Intel® USB 3.0 Drivers	62

IMPORTANT NOTE:

After installing your Windows operating system, you must install first the Intel Chipset Software Installation Utility before proceeding with the drivers installation.

Intel Chipset Software Installation Utility

The Intel Chipset Drivers should be installed first before the software drivers to enable Plug & Play INF support for Intel chipset components. Follow the instructions below to complete the installation.


1. Insert the DVD that comes with the board. Click **Intel** and then **Intel(R) Broadwell Chipset Drivers**.



2. Click **Intel(R) Chipset Software Installation Utility**.



3. When the Welcome screen to the Intel® Chipset Device Software appears, click **Next** to continue.
4. Click **Yes** to accept the software license agreement and proceed with the installation process.
5. On the Readme File Information screen, click **Next** to continue the installation.



6. The Setup process is now complete. Click **Finish** to restart the computer and for changes to take effect.

VGA Drivers Installation


1. Insert the DVD that comes with the board. Click **Intel** and then **Intel(R) Broadwell Chipset Drivers**.



2. Click **Intel(R) HD Graphics Driver**.




3. When the Welcome screen appears, click *Next* to continue.
4. Click *Yes* to agree with the license agreement and click *Next* to continue the installation.



6. On the screen shown below, click *Install* to continue.



7. Setup complete. Click **Finish** to restart the computer and for changes to take effect.



Realtek HD Audio Driver Installation

1. Insert the DVD that comes with the board. Click *Intel* and then *Intel(R) Broadwell Chipset Drivers*.




2. Click *Realtek High Definition Audio Driver*.



3. On the Welcome to the InstallShield Wizard screen, click **Next** to proceed with and complete the installation process.



4. The InstallShield Wizard Complete. Click **Finish** to restart the computer and for changes to take effect.



LAN Drivers Installation


1. Insert the DVD that comes with the board. Click **Intel** and then **Intel(R) Broadwell Chipset Drivers**.




2. Click **Intel(R) PRO LAN Network Driver**.




3. When the Welcome screen appears, click *Next*.
4. Click *Next* to agree with the license agreement.
5. Click the checkbox for **Drivers** in the Setup Options screen to select it and click *Next* to continue.



7. The wizard is ready to begin installation. Click **Install** to begin the installation.



8. When InstallShield Wizard is complete, click **Finish**.



Intel® Management Engine Interface




The following application requires Microsoft .NET Framework 3.5 or later: Intel® Management Engine Components. Please install the latest version of Microsoft .NET Framework from Microsoft Download Center to run this application correctly.

Follow the steps below to install the Intel Management Engine.


1. Insert the DVD that comes with the board. Click *Intel* and then *Intel(R) Broadwell Chipset Drivers* and then *Intel(R) ME 9.x Drivers*.



2. When the Welcome screen to the InstallShield Wizard for Intel® Management Engine Components, click the checkbox for **Install Intel® Control Center** & click **Next**.



3. Click **Yes** to to agree with the license agreement.



4. When the Setup Progress screen appears, click *Next*. Then, click *Finish* when the setup progress has been successfully installed.



Intel® USB 3.0 Drivers

1. Insert the DVD that comes with the board. Click **Intel** and then **Intel(R) Broadwell Chipset Drivers**



2. Click **Intel(R) USB 3.0 Drivers**.



3. When the Welcome screen to the InstallShield Wizard for Intel® USB 3.0 eXtensible Host Controller Driver, click *Next*.



4. Click *Yes* to agree with the license agreement and continue the installation.



5. On the Readme File Information screen, click *Next* to continue the installation of the Intel® USB 3.0 eXtensible Host Controller Driver.

6. Setup complete. Click *Finish* to restart the computer and for changes to take effect.



Appendix

A. I/O Port Address Map

Each peripheral device in the system is assigned a set of I/O port addresses which also becomes the identity of the device. The following table lists the I/O port addresses used.

Address	Device Description
000h - 01Fh	DMA Controller #1
000h - CF7h	PCI bus
040h - 043h	System timer
070h - 077h	System CMOS/real time clock
081h - 091h	DMA Controller #2
0F0h - 0F0h	Numeric data processor
2E0h - 2E7h	Communications Port (COM6)
2F8h - 2FFh	Communications Port (COM2)
3B0h- 3BBh	Intel(R) Iris(TM) Pro Graphics 6200
3F8h - 3FFh	Communications Port (COM1)

B. Interrupt Request Lines (IRQ)

Peripheral devices use interrupt request lines to notify CPU for the service required. The following table shows the IRQ used by the devices on board.

Level	Function
IRQ0	System Timer
IRQ3	Communications Port (COM2)
IRQ4	Communications Port (COM1)
IRQ8	System CMOS/real time clock
IRQ13	Numeric data processor
IRQ22	High Definition Audio Controller

C. Watchdog Timer Configuration

The WDT is used to generate a variety of output signals after a user programmable count. The WDT is suitable for use in the prevention of system lock-up, such as when software becomes trapped in a deadlock. Under these sorts of circumstances, the timer will count to zero and the selected outputs will be driven. Under normal circumstance, the user will restart the WDT at regular intervals before the timer counts to zero.

SAMPLE CODE:

```
//-----
//
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR
// PURPOSE.
//
//-----
#include <dos.h>
#include <conio.h>
#include <stdio.h>
#include <stdlib.h>
#include "F81866.H"
//-----
int main (int argc, char *argv[]);
void EnableWDT(int);
void DisableWDT(void);
//-----
int main (int argc, char *argv[])
{
    unsigned char bBuf;
    unsigned char bTime;
    char **endptr;

    char SIO;

    printf("Fintek 81866 watch dog program\n");

    SIO = Init_F81866();
    if (SIO == 0)
    {
        printf("Can not detect Fintek 81866, program abort.\n");
        return(1);
    }/if (SIO == 0)

    if (argc != 2)
    {
        printf(" Parameter incorrect!!\n");
        return (1);
    }

    bTime = strtol (argv[1], endptr, 10);
    printf("System will reset after %d seconds\n", bTime);

    if (bTime)
    {
        EnableWDT(bTime); }
    else
    {
        DisableWDT(); }

    return 0;
}
```

```

}
//-----
void EnableWDT(int interval)
{
    unsigned char bBuf;

    bBuf = Get_F81866_Reg(0x2B);
    bBuf &= (~0x20);
    Set_F81866_Reg(0x2B, bBuf); //Enable WDTO

    Set_F81866_LD(0x07); //switch to logic device 7
    Set_F81866_Reg(0x30, 0x01); //enable timer

    bBuf = Get_F81866_Reg(0xF5);
    bBuf &= (~0x0F);
    bBuf |= 0x52;
    Set_F81866_Reg(0xF5, bBuf); //count mode is second

    Set_F81866_Reg(0xF6, interval); //set timer

    bBuf = Get_F81866_Reg(0xFA);
    bBuf |= 0x01;
    Set_F81866_Reg(0xFA, bBuf); //enable WDTO output

    bBuf = Get_F81866_Reg(0xF5);
    bBuf |= 0x20;
    Set_F81866_Reg(0xF5, bBuf); //start counting
}
//-----
void DisableWDT(void)
{
    unsigned char bBuf;

    Set_F81866_LD(0x07); //switch to logic device 7

    bBuf = Get_F81866_Reg(0xFA);
    bBuf &= ~0x01;
    Set_F81866_Reg(0xFA, bBuf); //disable WDTO output

    bBuf = Get_F81866_Reg(0xF5);
    bBuf &= ~0x20;
    bBuf |= 0x40;
    Set_F81866_Reg(0xF5, bBuf); //disable WDT
}
//-----

```



```

//-----
//
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR
// PURPOSE.
//
//-----
#include "F81866.H"
#include <dos.h>
//-----
unsigned int F81866_BASE;
void Unlock_F81866 (void);
void Lock_F81866 (void);
//-----
unsigned int Init_F81866(void)
{
    unsigned int result;
    unsigned char ucDid;

    F81866_BASE = 0x4E;
    result = F81866_BASE;

    ucDid = Get_F81866_Reg(0x20);
    if (ucDid == 0x07) //Fintek 81866
    {
        goto Init_Finish;
    }

    F81866_BASE = 0x2E;
    result = F81866_BASE;

    ucDid = Get_F81866_Reg(0x20);
    if (ucDid == 0x07) //Fintek 81866
    {
        goto Init_Finish;
    }

    F81866_BASE = 0x00;
    result = F81866_BASE;
}

Init_Finish:
    return (result);
}
//-----
void Unlock_F81866 (void)
{
    outportb(F81866_INDEX_PORT, F81866_UNLOCK);
    outportb(F81866_INDEX_PORT, F81866_UNLOCK);
}
//-----
void Lock_F81866 (void)
{
    outportb(F81866_INDEX_PORT, F81866_LOCK);
}
//-----
void Set_F81866_LD( unsigned char LD)
{
    Unlock_F81866();
    outportb(F81866_INDEX_PORT, F81866_REG_LD);
    outportb(F81866_DATA_PORT, LD);
    Lock_F81866();
}
//-----
void Set_F81866_Reg( unsigned char REG, unsigned char DATA)
{
    Unlock_F81866();
    outportb(F81866_INDEX_PORT, REG);
    outportb(F81866_DATA_PORT, DATA);
    Lock_F81866();
}
//-----

```

```

unsigned char Get_F81866_Reg(unsigned char REG)
{
    unsigned char Result;
    Unlock_F81866();
    outportb(F81866_INDEX_PORT, REG);
    Result = inportb(F81866_DATA_PORT);
    Lock_F81866();
    return Result;
}
//-----

//-----
//
// THIS CODE AND INFORMATION IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY
// KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE
// IMPLIED WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR A PARTICULAR
// PURPOSE.
//
//-----
#ifndef __F81866_H
#define __F81866_H                1
//-----
#define F81866_INDEX_PORT        (F81866_BASE)
#define F81866_DATA_PORT        (F81866_BASE+1)
//-----
#define F81866_REG_LD            0x07
//-----
#define F81866_UNLOCK            0x87
#define F81866_LOCK              0xAA
//-----
unsigned int Init_F81866(void);
void Set_F81866_LD( unsigned char);
void Set_F81866_Reg( unsigned char, unsigned char);
unsigned char Get_F81866_Reg( unsigned char);
//-----
#endif __F81866_H

```