

## NP102-N16C Intel® 945GSE Mini-ITX Board

### PROCESSOR

- Intel® Atom™ N270 processor
- 1.6GHz core frequency, 1.10V voltage
- 2.5W thermal design power
- 512KB on-die L2 cache
- 533MHz FSB
- 22x22 mm, 1.0 mm ball pitch and 437 balls FCBGA

### CHIPSET

- Intel® chipset
  - Intel® 945GSE Graphics Memory Controller Hub (GMCH)
  - Intel® ICH7M I/O Controller Hub

### SYSTEM MEMORY

- One 240-pin DDR2 DIMM socket
- Supports DDR2 400/533MHz
- Supports up to 2GB system memory

### EXPANSION SLOTS

- 1 PCI Express x1 slot
- 1 PCI slot
- 1 CompactFlash socket

### ONBOARD GRAPHICS FEATURES

- Intel GMA 950
- 133/166MHz internal graphics core render frequency at 1.05V core voltage
- 24-bit dual-channel LVDS
- CRT resolutions up to SXGA+

### ONBOARD AUDIO FEATURES

- Realtek ALC262 2-channel High Definition Audio
- Two 24-bit stereo DACs and three 20-bit stereo ADCs
- S/PDIF audio interface

### ONBOARD LAN FEATURES

- Two Realtek RTL8111C PCI Express Gigabit Ethernet controllers
- 10Mbps, 100Mbps and 1Gbps data transmission
- IEEE 802.3 (10/100Mbps) and IEEE 802.3ab (1Gbps) compliant

### SERIAL ATA INTERFACE

- Two SATA ports with independent DMA operation supported on ports 0 and 2
- Two-mode operation supports legacy mode using I/O space or an AHCI mode using memory space
- SATA and PATA can be used in a combined function mode (When SATA is used with PATA, AHCI mode is not supported.)

### IDE INTERFACE

- Bus Master IDE (PATA) controller
- Supports up to two IDE devices
- Ultra ATA 100/66/33

### REAR PANEL I/O PORTS

- 1 mini-DIN-6 PS/2 mouse port
- 1 mini-DIN-6 PS/2 keyboard port
- 2 DB-9 RS232/422/485 serial ports
- 1 DB-15 VGA port
- 2 RJ45 LAN ports
- 4 USB 2.0/1.1 ports
- Mic-in, line-in and line-out

### I/O CONNECTORS

- 2 connectors for 4 external USB 2.0/1.1 ports
- 2 connectors for 2 external RS232 serial ports
  - Pins 1 and 9 of COM3 functions as RS232 signal or power (selectable via jumper)
- 1 LVDS LCD panel connector
- 1 LCD/inverter power connector
- 1 8-bit Digital I/O connector
- 1 front audio connector for line-out and mic-in jacks
- 1 CD-in connector
- 1 S/PDIF connector
- 2 Serial ATA connectors
- 1 40-pin IDE connector
- 1 24-pin ATX power connector
- 1 front panel connector
- 1 chassis intrusion connector
- 1 fan connector

### BIOS

- Award BIOS
- 8Mbit SPI BIOS

### ENERGY EFFICIENT DESIGN

- ACPI 2.0/1.0 specification
- Wake-On-Events include:
  - Wake-On-PS/2 Keyboard/Mouse
  - Wake up by PCI card
  - PCI Express PME
  - USB KB/MS wake up from S3
  - Wake-On-Ring
  - RTC timer to power-on the system
- Enhanced Intel® SpeedStep Technology
- AC power failure recovery

### DAMAGE FREE INTELLIGENCE

- Monitors CPU/system temperature and overheat alarm
- Monitors CPU(V)/3.3V/5V/12V/VBAT(V) voltages and failure alarm
- Monitors system fan speed and failure alarm
- Read back capability that displays temperature, voltage and fan speed
- Watchdog timer function

### TEMPERATURE

- 0°C to 60°C

### HUMIDITY

- 10% to 90%

### PCB

- Mini-ITX form factor
- 170mm (6.7") x 170mcm (6.7")

### REAR PANEL I/O PORTS

