


GIGABYTE™

GA-SBC7100 Intel® KabyLake-U MCP Embedded SBC MB

Overview



Rear I/O




Product Feature

- Intel® Kaby lake ULT Core i3-7100U MCP Processor
- Integrated Intel® Gen 8 Graphics DX 12*, OGL4.5
- Supports Dual Channel DDR4 2133 MHz, 2 x SO-DIMM, up to 16GB system memory
- 1 x HDMI1.4a, 1x Display port, 1 x Dual Channel 24-bit LVDS
- 4 x USB 3.0, 4 x USB 2.0, 2 x SATA3
- 1 x mini-PCIe, solt co-lay with mSATA
- Gigabit LAN : 2 x Intel® Lan
- 1 x TPM2.0 Module IC (Optional)
- 9-36 V DC-in

SPEC

Form Factor	PCB Size	SBC (5.74 x 4 inch) (146 x 102 mm)
Processor System	CPU	Intel® Core I series kaby lake U i3-7100U MCP Processor
		Supports Hyper-Threading Technology
		Default i3-7100 Quad core 15W processor
Expansion Slot	PCI	0
	Mini-PCIe	1x Full size mini-PCIe slot, co-lay with mSATA
	PCIe	0
	M.2	1 x M.2 2280 slot for storage 1 x M.2 Wifi slot
Memory	Technology	Dual Channel DDR4 2133 MHz SDRAM
	Max.	16G
Graphics	Controller	Intel® Gen8 Intel Graphics DX 12*, OGL4.5
	VRAM	Shared Memory
	VGA	N/A
	LVDS	Dual channel 24-bit, max resolution 1920 x 1200@60Hz
	HDMI	Yes
	DVI	No
	Display Port	Yes, max resolution 4096x2304@60Hz
	Multi Display	Yes (Dual Display)
LAN	Controller	1 x Intel i211AT, 1 x Intel i219V
SATA	Max DTR	SATA3 (6.0Gb/s)
	VGA	0
Rear I/O	HDMI	1
	Display Port	1
	Ethernet	2
	USB	4 x USB 3.0
	Audio	0
	Serial	0
	USB	4 x USB 2.0 compliant
Internal Connector	LVDS/Inverter	1
	VGA	0
	Serial	4 x RS-232 (COM1/2 support RS-232/RS-422/485)
	SATA	2 x SATA3 (6.0Gb/s)
	Mini-PCIe	1(1 x co-lay with mSATA SSD)
	Parallel	0
	Digital I/O	4 in/4 out
	I2C/SMBUS	1
SATA PWR Output Con	1	
Watchdog Timer	Output	From Super I/O to drag RESETCON#
	Interval	256 segments, 0,1,2...255sec/min
Power Requirements	Input PWR	9~36V DC-in 4-pin PWR connector (co-lay with Pheonix connector)
	Power On	AT/ATX Supported
		AT: Directly PWR on as Power input ready ATX: Press Button to PWR on after Power input ready
Power consumption	Typical	TBD
Certification	EMC	CE/FCC
Environment	Operating Temperature	0°C - 60°C

Mechanism Drawing



Ordering Information

Model Name	Ordering Information
GA-SBC7100	KabyLake-U, 2 x DDR4 SoDIMM, HDMI, Dual channel 24 bit LVDS, DP, SATA3, Dual LAN, 4 x USB3.0, 4 x USB2.0 Mini PCIe/mSATA, M.2 WIFI, M.2 SSD, DC in 9~36V, 0~60 degree, TPM, 4 in/4out DIO, I2C, SMBUS

Optional Accessories

Part Number	Cable Usage	Description
12CF1-1CM011-01R	COM	11N1 CB/JST 2*5P/PH2/KIMWELL COM 9MA(PC99)/200mm+SCREW*2
12CF1-2SAT1B-01R	SATA	2IN1 CB/SATA(S)/BLACK/CODE CPU90*180*1/180*180*1/2H*8P/50 CM
12CF1-1SATPW-91R	SATA Power	11N1 CB FOR SATA POWER/KIMWELL
12CR1-1AU001-21R	AUDIO Cable	AUDIO*2(LINE OUT/MIC)/KIMWELL

* The entire materials provided herein are for reference only. GIGABYTE reserves the right to modify or revise the content at anytime without prior notice. * Advertised performance is based on maximum theoretical interface values from respective Chipset vendors or organization who defined the interface specification. Actual performance may vary by system configuration. * All trademarks and logos are the properties of their respective holders. * Due to standard PC architecture, a certain amount of memory is reserved for system usage and therefore the actual memory size is less than the stated amount.