



## Specifications

Display & Touch Screen	Display Size	15.6" TFT-LCD
	Max. Resolution	1920 x 1080
	Luminance (cd/m2)	300
	Contrast	700:1
	Max. Color	262K
	View Angle (H/V)	178/178
	Backlight Lifetime(hrs)	15000
	Touch Type	Projected capacitive
	Touch Interface	USB
	Light Transmission (%)	90%
Point of touch	10	
External I/O Port	Signal input	VGA/DVI
	USB	1x USB for touch/RFID/camera 1x USB Hub
	Audio	1x Audio
	Power Connector	Power jack
Mechanical	Dimensions (mm)	397.7 x 287 x 45
	Net Weight (kgs)	4.5
System	Membrane Control	Menu/Enter, Left/Up, Right/Down, Power on/off
	RFID	1x 13.56 MHz RFID Reader
	Built-in Camera	1x 1920 x 1080 front web camera
	Built-in Speaker/Mic	2x Speaker
Power	Power Input Range	12V DC Input
Construction	Chassis Material	SGCC
	Color (Front/Back)	Black
	IP Rating	IP65 front bezel
	Mounting	VESA 75x75, 100x100 mm
Environmental	Operating Temperature	0°C~50°C
	Storage Temperature	-20°C~60°C
	Storage Humidity	10%~90% (non-condensing)
	Certification	CE/FCC Class A

## Features

- Flat Panel Design
- Projected Capacitive Touch
- Multiple signal interfaces with VGA & DVI
- Built-in 13.56 MHz RFID reader
- Supports 1920 x 1080 front web camera
- OSD Keypad Control at top side
- DC 12V Power Input



## Ordering Information

IPPD1560RF

15.6" FHD Flat Panel Design Monitor, projected capacitive touch, VGA, DVI, Audio, OSD keypad, camera and RFID reader, 12V DC power input with power adapter

## Dimensions

