

# SPECIFICATION



ESD14004084

FSP460-701UH



**全漢企業股份有限公司**  
**FSP TECHNOLOGY INC.**

台灣 桃園市建國東路 22 號

NO.22, Jianguo E. Rd., Taoyuan City, Taiwan, R.O.C.  
TEL:+886-3-375-9888 FAX:+886-3-375-6966

# SPECIFICATION

## **FSP460-701UH**

**Main Feature:**  
**Active PFC Circuit**  
**Full Range Input**

**DEC,30,2013**

**REV: 1.7**



全漢企業股份有限公司  
FSP TECHNOLOGY INC.

**MODEL: FSP460-701UH**

**Revision History**

<u>Rev</u>	<u>Description</u>	<u>Date</u>	<u>Author</u>
01	ITEM4.4 ADD: Standby efficiency should be greater than 50% with a minimum loading of 100Ma at 230V/50Hz.	6/17	KELLY
02	4.1.5.OVER CURRENT PROTECTION修改12V OCP為18-22A	8/11	KELLY
03	OUTPUT RATING 5.1V 改為 5V	8/24	KELLY
04	4.4 Item add EUP spec	12/24	DANNY
1.5	DEL 3.2 CONNECTOR SPECIFICATIONS 4.1.3. HOLD-UP TIME (@50%-->FULL LOAD)	2010.12.02	Winnie (Andy)
1.6	4.1.1. OUTPUT RATING(3.3V→0.3A)	2012.03.08	Winnie (Andy)
1.7	ADD 5.5 ALTITUDE	2013.12.30	Winnie (Andy)

## **1. GENERAL DESCRIPTION AND SCOPE**

This is the specification of Model FSP460-701UH AC-line powered switching power supply with active PFC (Power Factor Correction) circuit, meet EN61000-3-2 and with Full Range Input features. Designed and manufactured by FSP GROUP.

The specification below is intended to describe as detailedly as possible the functions and performance of the subject power supply. Any comment or additional requirements to this specification from our customers will be highly appreciated and treated as a new target for us to approach.

## **2. REFERENCE DOCUMENTS**

The subject power supply will meet the EMI requirements and obtain main safety approvals as following:

### **2.1 EMI REGULATORY**

- FCC Part 15 Subpart J, Class 'B' 115 Vac operation.
- CISPR 22 Class 'B' 230 Vac operation.

## **3. PHYSICAL REQUIREMENTS**

### **3.1 MECHANICAL SPECIFICATIONS**

The mechanical drawing of the subject power supply, which indicate the form factor, location of the mounting holes, location, the length of the connectors, and other physical specifications of the subject power supply. Please refer to the attachment drawing.

## **4. ELECTRICAL REQUIREMENTS**

### **4.1 OUTPUT ELECTRICAL REQUIREMENTS**

The subject power supply will meet all electrical specifications below, over the full operation temperature range and dynamic load regulation.

## 4.1.1. OUTPUT RATING

Output	Nominal	Regulation	Ripple/Noise	Min	Max	peak
1	+3.3V	3.3V ±5%	50mV	0.3A	20.0 A	
2	+5V	+5V ±5%	50mV	1.0A	20.0 A	
3	+12V1	12V ±5%	120mV	0.5A	16.0 A	
4	+12V2	12V ±5%	120mV	1.0A	16.0 A	
5	+12V3	12V ±5%	120mV	1.0A	16.0 A	
6	-12V	-12V ±10%	120mV	0 A	0.5 A	
7	+5Vsb	+5Vsb ±5%	50mV	0 A	3.0A	

- (1) Maximum continuous total DC output power should not exceed 460W.
- (2) Maximum continuous load on the combined 12V1,12V2,12V3 output shall not exceed 35A.
- (3) Combined 3.3V and 5V power shall not exceed 130W.
- (4) Ripple and noise measurements shall be made under all specified load conditions through a single pole low pass filter with 20MHz cutoff frequency. Outputs shall bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading

## 4.1.2. LOAD CAPACITY SPECIFICATIONS

The cross regulation defined as follows, the voltage regulation limits DC include DC Output ripple & noise.

LOAD	STM.	+3.3V	+5V	+12V1	+12V2	+12V3	-12V	+5Vsb
ALL MAX	HHHHHH	12.62A	12.62A	9.40A	9.40A	9.40A	0.4A	2.42A
+5V MAX other MIN	LHLLLL	0.3A	20.0 A	0.5A	1.0A	1.0A	0A	0A
+3.3V MAX other MIN	HLLLLL	20.0 A	1.0 A	0.5A	1.0A	1.0A	0A	0A
+12V1 MAX other MIN	LLHLLL	0.3A	1.0A	16.0A	1.0A	1.0A	0A	0A
+12V2 MAX other MIN	LLLHLL	0.3A	1.0 A	0.5A	16.0A	1.0A	0A	0A
+12V3MAX other MIN	LLLHL	0.3A	1.0 A	0.5A	1.0A	16.0A	0A	0A
ALL MIN	LLLLLL	0.3A	1.0 A	0.5A	1.0A	1.0A	0A	0A

## 4.1.3. HOLD-UP TIME (@FULL LOAD)

115V / 60Hz : 16 mSec. Minimum.

230V / 50Hz : 16 mSec. Minimum.

The output voltage will remain within specification, in the event that the input power is removed or interrupted, for the duration of one cycle of the input frequency. The interruption may occur at any point in the AC voltage cycle. The power good signal shall remain high during this test.

## 4.1.4.OUTPUT RISE TIME

(10% TO 90% OF FINAL OUTPUT VALUE, @FULL LOAD)

115V-rms or 230V-rms + 5Vdc : 20ms Maximum

## 4.1.5.OVER VOLTAGE PROTECTION

Voltage Source	Protection Point
+ 3.3 V <sub>dc</sub>	3.5V-4.5V
+5V <sub>dc</sub>	5.5V-6.82V
+12V <sub>1dc</sub> , +12V <sub>2dc</sub> , +12V <sub>3dc</sub>	13.4V-15.6V

## 4.1.6.SHORT CIRCUIT PROTECTION

Output short circuit is defined to be a short circuit load of less than 0.1 ohm.

In the event of an output short circuit condition on +3.3V, +5V or +12V output, the power supply will shutdown and latch off without damage to the power supply. The power supply shall return to normal operation after the short circuit has been removed and the power switch has been turned off for no more than 2 seconds.

In the event of an output short circuit condition on -12V output, the power supply will not be damaged. The power supply shall return to normal operation as soon as the short circuit has been removed. and the power switch has been turned off for no more than 2 seconds.

## 4.1.7.OVER CURRENT PROTECTION

3.3V	25A-40A
5V	25A-40A
12V1	18A-22A
12V2	18A-22A
12V3	18A-22A


## 4.1.8.POWER GOOD SIGNAL

The power good signal is a TTL compatible signal for the purpose of initiating an orderly star-up procedure under normal input operating conditions. This signal is asserted (low) until +5Vdc has reached 4.75 volts during power up. Characteristics:


TTL signal asserted (low state) : less than 0.5V while sinking 10mA.  
 TTL signal asserted (high state): greater than 4.75V while sourcing 500uA.  
 High state output impedance: less or equal to 1Kohm from output to common.

POWER GOOD @ 115/230V, FULL LOAD	100 –500mSec.
POWER FAIL @115/230V, FULL LOAD	1 mSec. minimum

(A) Remote ON-OFF Timing:



(B) AC ON / OFF Timing :



#### 4.2. OUTPUT TRANSIENT LOAD RESPONSE

The output voltages shall remain within the limits specified in 4.1.1 output rating table in page 6 for the step loading and within the limits specified in Table 1 for the capacitive loading. The load transient repetition rate shall be tested between 50Hz and 5 kHz at duty cycles ranging from 10%-90%. The load transient repetition rate is only a test specification. The step load may occur anywhere within the MIN load to the MAX load shown in Table 1.

**Table 1: Transient Load Requirements**

Output	Step Load Size	Load Slew Rate	Capacitive Load
+3.3V	30% of max load	0.5A/us	1000uF
+5V	30% of max load	0.5A/us	1000uF
+12V1,+12V2,+12V3	65% of max load	1.0A/us	2200uF
+5Vsb	25% of max load	0.5A/us	100uF

#### 4.3. INPUT ELECTRICAL SPECIFICATIONS

##### 4.3.1. VOLTAGE RANGE

PARAMETER		UNITS
V-in Range	90 - 264	V-rms

##### 4.3.2. INPUT FREQUENCY

INPUT FREQUENCY	47-63Hz
-----------------	---------

##### 4.3.3. INRUSH CURRENT

(Cold start – 25 deg. C)

115V	40A
230V	80A

(No damage)

##### 4.3.4. INPUT LINE CURRENT

115V	8Amps – rms maximum
230V	4 Amps – rms maximum

#### 4.4. EFFICIENCY

	Full load (100%)	Typical load (50%)	Light load (20%)
115VAC	82%	85%	82%
230VAC	82%	85%	82%

**Standby Power Consumption (5Vsb):**



Input Power < 1W @ 5Vsb/100mA & 230Vac input

PS\_ON input signal @ High State

(loading shown in Amps)

Loading	+12V1	+12V2	+12V3	+5V	+3.3V	-12V	+5Vsb
Full (100%)	9.40	9.40	9.40	12.62	12.62	0.4	2.42
Typical (50%)	4.72	4.72	4.72	6.31	6.31	0.2	1.21
Light (20%)	1.88	1.88	1.88	2.52	2.52	0.08	0.48

#### 4.6. PS\_ON#

PS\_ON# is an active-low, TTL-compatible signal that allows a motherboard to remotely control the power supply in conjunction with features such as soft on/off, Wake on LAN+, or wake-on-modem. When PS\_ON# is pulled to TTL low, the power supply should turn on the five main DC output rails: +12VDC,+5VDC,+3.3VDC,-5VDC,and -12VDC. When PS\_ON# is pulled to TTL high or open-circuited, the DC output rails should not deliver current and should be held at zero potential with respect to ground. PS\_ON# has no effect on the +5VSB output, which is always enabled whenever the AC power is present. Table 15 lists PS\_ON# signal characteristics.

The power supply shall provide an internal pull-up to TTL high. The power supply shall also provide debounce circuitry on PS\_ON# to prevent it from oscillating on/off at startup when activated by a mechanical switch. The DC output enable circuitry must be SELV-compliant.

**Table 15. PS\_ON# Signal Characteristics**

	Min.	Max.
VIL, Input Low Voltage	0.0V	0.8V
IIL, Input Low Current (Vin = 0.4V)		-1.6mA
VIH, Input High Voltage (Iin = -200 μA)	2.0V	
VIH OPEN circuit, Iin = 0		5.25V

### 5. ENVIRONMENTAL REQUIREMENTS

The power supply will be compliant with each item in this specification for the following Environmental conditions.

#### 5.1. TEMPERATURE RANGE

Operating	0 to +50 deg. C
Storage	-20 to +80 deg. C

## 5.2. HUMIDITY

Operating	85% RH, Non-condensing
Storage	95% RH, Non-condensing

## 5.3. VIBRATION

The subject power supply will withstand the following imposed conditions without experiencing non-recoverable failure or deviation from specified output characteristics.

Vibration Operating – Sine wave excited, 0.25 G maximum acceleration, 10-250 Hz swept at one octave / min. Fifteen minute dwell at all resonant points, where resonance is defined as those exciting frequencies at which the device under test experiences excursions two times large than non-resonant excursions.

Plane of vibration to be along three mutually perpendicular axes.

## 5.4. SHOCK

The subject power supply will withstand the following imposed conditions without experiencing non-recoverable failure or deviation from specified output characteristics.

Storage 40G, 11 mSec. half-sine wave pulse in both directions on three mutually perpendicular axes.

Operating 10G, 11mSec. half-sine wave pulse in both directions on three mutually Perpendicular axes.

## 5.5 ALTITUDE

The power supply is applied for tropical climates and use at altitudes not exceeding 5000m above Sea level

## 6. SAFETY

### 6.1. LEAKAGE CURRENT

The leakage current from AC to safety ground will not exceed 3.5 mA-rms at 264Vac, 50 Hz.

## 7. ELECTROMAGNETIC COMPATIBILITY

### 7.1 LINE CONDUCTED EMI

The subject power supply will meet FCC and VFG class B requirements under full load conditions.

## 7.2. RADIATED EMI

The subject power supply will meet FCC and CISPR 22 requirements under normal load conditions.

## 8. LABELLING

Label marking will be permanent, legible and complied with all agency requirements.

### 8.1. MODEL NUMBER LABEL

Labels will be affixed to the sides of the power supply showing the following:

- Manufacturer's name and logo.
- Model no., serial no., revision level, location of manufacturer.
- The total power output and the maximum load for each output.
- AC input rating.

### 8.2 DC OUTPUT IDENTIFICATION

Each output connector will be labeled.

## 9. RELIABILITY

### 9.1. MTBF

The power supply have a minimum predicted MTBF(MIL-HDBK-217) of 100,000 hours of continuous operation at 25°C, 75% -output load, and nominal AC input voltage.