

Datasheet

M.2 (S42) 3IE6-P series

- SATA III solution for industrial field
- Exclusive L³ architecture
- Excellent random performance
- Supports TRIM/NCQ/SMART
- Built in iData Guard
- Compatible with M.2 2242-D2-B-M standard
- Designed with hardware LDPC ECC engine




Introduction

Innodisk M.2 (S42) 3IE6-P is SATA III 6.0 Gb/s flash based disk, which delivers excellent performance, especially in random data transfer rate, and which offers reliability making it the ideal solution for a variety of applications, including embedded system, industrial computing, and enterprise field. M.2 (S42) 3IE6-P not only performs unmatched performance, but also designed with Innodisk owned technical knowhow to ensure the data integrity and highest levels of reliability.

Innodisk M.2 (S42) 3IE6-P is designed for industrial field, and supports several standard features, including TRIM, NCQ, and S.M.A.R.T. In addition, Innodisk's exclusive industrial-oriented firmware provides a flexible customization service, making it perfect for a variety of industrial applications.

M.2 (S42) 3IE6-P series

Diagram



Contact us for more information about the M.2 (S42) 3IE6-P

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
Tel: +886-2-7703-3000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421

Europe
eusales@innodisk.com
+31-40-3045-400

Japan
jpsales@innodisk.com
+81-3-6667-0161

China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2021 Innodisk Corporation.
All right reserved. Specifications are subject to change without prior notice.

Specifications

Interface	SATA III
Flash Type	iSLC (3D TLC)
P/E cycle	30,000
Capacity	80GB~160GB
Max. Channels	4
Sequential R/W (MB/sec, max.)	550/490
Max. Power Consumption	2.0W
Thermal Sensor	✓
External DRAM buffer	✓
H/W Write Protect	-
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	22.0 X 42.0 X 3.5 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -40°C ~ +85°C MTBF: 3 million hours

Ordering Information

Operation Temp.	80GB	160GB
Standard Grade (0°C ~ +70°C)	DHM24-80GM71EC*QF	DHM24-A60M71EC*QF
Industrial Grade (-40°C ~ +85°C)	DHM24-80GM71EW*QF	DHM24-A60M71EW*QF

*: PCB version