




ESM-SKLA

6th Gen Intel® Xeon® E3-1500 series /Core™ Processor i3 series Type6 COMe Basic Module with Intel® CM236 Chipset



- > Onboard 6th Gen Intel® Xeon® E3-1500 series / Core™ i3 series Processor
- > Two 260-pin SODIMM DDR4 SDRAM slot up to 32GB, CM236 Support ECC Function
- > Dual-channel 18/24-bit LVDS, VGA, DP/HDM/DVI, eDP Option
- > Intel® I219LM Gigabit Ethernet
- > 8 PCIe x1, 1 PCIe x16, 4 SATA, 8 USB 2.0, 4 USB 3.0
- > HD Audio Interface
- > Type 6 Rev 2.1 Pin-out
- > TPM 2.0

+ Spec

System Information	
Processor	6th Gen Intel® Xeon® E3-1505M v5 4-Core 2.8GHz processor 6th Gen Intel® Xeon® E3-1505Lv5 , 4-Core 2.0GHz Processor 6th Gen Intel® Core™ i3-6100E , 2-Core, 2.7GHz Processor 6th Gen Intel® Core™ i3-6102E , 2-Core, 1.9 GHz Processor
Platform Controller Hub	Intel® CM236 Express Chipset
System Memory	2 x 260-Pin DDR4 2133MHz SO-DIMM up to 32 GB (CM236 Support ECC Function)
I/O Chipset	EC ITE IT8528E
BIOS Information	AMI uEFI BIOS, 128Mbit SPI Flash ROM
Expansion	
Expansion	8 x PCIe x1
I/O	
USB Port	8 x USB 2.0 4 x USB 3.0
COM Port	2 x UART
SATA	4 x SATA III
DIO	1 x 8bit GPIO
MIO	1 x SMBus 1 x LPC 1 x I2C
Display	
Graphic Chipset	Intel® Skylake SoC integrated Graphics
Spec. & Resolution	VGA: Max. resolution 1920x1080 @ 60Hz LVDS: Max. resolution 1920x1080 @ 60Hz HDMI: Max. resolution 4096x2304 @ 24Hz (HDMI Max resolution only one display output)
Multiple Display	(VGA + DP) + HDMI + DDI LVDS + (VGA + DP) + DDI LVDS + (VGA + DP) + HDMI LVDS + HDMI + DDI
LVDS	CH7511B(eDP to LVDS)
DDI	HDMI DVI DisplayPort
Audio	
Audio Interface	Intel® High Definition Audio
Certifications	
Certification Information	CE FCC Class B
Ethernet	
LAN Chipset	1 x Intel® I219LM
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
Mechanical & Environmental	
Operating Temperature	0°C ~ 60°C (32°F ~ 140°F)(Standard)
Storage Temperature	-40°C ~ 75°C (-40°F ~ 167°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	0.44lbs(0.2kg)
Power Requirement	+9V ~ +19V
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI 3.0 Compliant
Power Mode	AT/ATX
Dimension (L x W)	5" x 3.7" (125mm x 95mm)
Software Support	



OS Information	Win 7 / Win 8.1 / Win 10 / Linux
Ordering Information	
Ordering Information	<p>ESM-SKLA-05M-A1R Intel® Xeon® E3-1505M v5 Type6 COMe Basic Module</p> <p>ESM-SKLA-05L-A1R Intel® Xeon® E3-1505L v5 Type6 COMe Basic Module</p> <p>ESM-SKLA-6100-A1R Intel® Core™ i3-6100E Type6 COMe Basic Module</p> <p>EEV-EX14-B1R mATX Ev. Board for COMe Type 6 A1.1</p> <p>ACC-ESMSKLH-CL-1R Cooler for ESM-SKLH/ESM-SKLA W/FAN H=43.5mm</p> <p>ACC-ESMKBLH-SD-1R Heatspreader W/O FAN H=8.0mm (for ESM-KBLH/ESM-KBLA/ESM-SKLH/ESM-SKLA)</p>