M133WKU

13.3" industrial tablet with Intel® Core™ i5-8265U



KEY FEATURES

- Intel® Core™ i5-8265U Whiskey Lake processor industrial tablet
- 13.3" 1920 x 1080 IPS wide viewing angle LED Panel
- Magnesium alloy housing with all-around elastomeric rubber
- Built-in kickstand usable as carrying handle(indefinitely adjustable)
- Cold swap Battery Pack
- IP65 waterproof and dustproof
- Optical bonding technology
- TPM 2.0







SPECIFICATIONS

Display					
Resolution	1920x1080	Size	13.3 inches		
Contrast Ratio	1000:1	Panel Brightness	500 nits		
View Angles	89,89,89,89	Туре	Projected Capacitive Multi Touch		
Bonding	Optical Bonding for Sunlight Viewability				
System Specification					
Processor	Intel® CoreTM i5-8265U, 1.60 GHz (up to 3.90 GHz)	Memory	4GB SODIMM DDR4-2400 8GB SODIMM DDR4-2400 (Optional) 16GB SODIMM DDR4-2400 (Optional)		
Storage	Storage 1: 1 x 128GB M.2 SSD Additional storage available with SDXC card slot Storage 1 up to 1x 1TB M.2 SSD (Optional) Storage 2 up to 1x 1TB M.2 SSD (Optional)	Ethernet controller	1 x RJ45-10/100/1000 Mbps LAN		
Security	Trusted Platform Module (TPM) 2.0 Kensington Lock	Operating System	Ubuntu 18.04		
WLAN	Support	ВТ	Support		
WWAN	4G LTE (Optional)	GNSS	GPS/GLONASS (Optional)		
Mechanical					
Dimension	338.2 x 240 x 30 mm (13.3 x 9.4 x 1.18 inches)	Weight	2.2kg (w/ kickstand)		
Cooling System	Fanless thermal design				
IO Ports					
USB Port	4 x USB 3.0 Type A, 1 x USB 3.1 Type C	SD Card Slot	1 x SDXC Slot		
Audio	2 x 1 watt speaker	LAN	1 x RJ45-10/100/1000 Mbps LAN		
Indicator	4x LED Indicator for Power, Battery, SSD, RF status	Docking Connector	1 x Docking connector		
Environment					
Operating Humidity	30% to 80% RH, non-condensing	Operating Temperature	-10°C to 50°C (14°F to 122°F)		
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	Shock	MIL-STD-810G Method 516.6 Procedure I		
Vibration	MIL-STD-810G Method 514.6 Procedure I	IP rating	IP65 certified, dustproof and waterproof		


Drop

MIL-STD-810G Method 516.6, 4 ft

=				
Certification				
Certification	CE, FCC			
Security Function				
Kensington Lock	Kensington Lock Support			
Control				
Button	1 x Power,1 x menu,2 x volume key 3 x Programmable Function Keys			
Power				
Battery	15.4V, typ. 5900 mAh Li-Polymer Battery (4S1P)	Battery Operating Time	More than 10 hours (BAPCo Tabl etMark v3)	
Power Rating	19V DC	Adapter	100-240V, 50-60Hz / 19V DC	
Accessory				
Accessory	Adapter and Power Cord Standard Battery Stylus Stand with Integrated Handle	Optional Accessory	Vehicle Charger (Optional) Battery Charger (Optional) Desk Docking (Optional)	

DIMENSIONS UNIT:MM

Winmate M133WKU



NOTE

- 1. Total usable memory will be less dependent upon actual system configuration.
- 2. TPM 2.0 is available upon request.
- 3. Length measurements do not include protrusions. Weight varies with options.
- 4. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.
- 5. This is a simplified drawing and some components are not marked in detail.
- 6. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.