

WM343-CS330

H310
Q370

8th/9th Gen Intel® Core™
Desktop Box PC

KEY FEATURES



Upgraded CPU

Powered by 8th/9th Gen Intel® Core™




Triple Independent Display

VGA + DVI-D + DP++



4 Expansion Slots

3.5"/2.5" SATA + 5.25" optical drive bay



Multiple Expansion

Support 1 PCIe x16, 1 PCIe x4, 2 PCI, 1 Mini-PCIe socket




15 Years Long Term Support


15-Year CPU Life Cycle Support Until Q3' 33



PANEL




Front View




Rear View


DIMENSIONS




Rear View




Left View





Front View



Right View



WALL MOUNTING



SPECIFICATION

SYSTEM	Processor	8th Generation Intel® Core™ /Pentium®/Celeron® LGA 1151 Socket Processors: Intel® Core™ i7-8700K (6 Cores, 12M Cache, up to 4.7 GHz); 95W Intel® Core™ i7-8700 (6 Cores, 12M Cache, up to 4.6 GHz); 65W Intel® Core™ i7-8700T (6 Cores, 12M Cache, up to 4.0 GHz); 35W Intel® Core™ i5-8500 (6 Cores, 9M Cache, up to 4.1 GHz); 65W Intel® Core™ i5-8500T (6 Cores, 9M Cache, up to 3.5 GHz); 35W Intel® Core™ i3-8100 (4 Cores, 6M Cache, 3.6 GHz); 65W Intel® Core™ i3-8100T (4 Cores, 6M Cache, to 3.1 GHz); 35W Intel® Pentium® G5400 (2 Cores, 4M Cache, 3.7 GHz); 58W Intel® Pentium® G5400T (2 Cores, 4M Cache, 3.1 GHz); 35W Intel® Celeron® G4900 (2 Cores, 2M Cache, 3.1 GHz); 54W Intel® Celeron® G4900T (2 Cores, 2M Cache, 2.9 GHz); 35W 9th Generation Intel® Core™ LGA 1151 Socket Processors: Intel® Core™ i9-9900K (8 Cores, 16M Cache, up to 5.0 GHz); 95W (Non-LTS) Intel® Core™ i7-9700TE (8 Cores, 12M Cache, up to 3.8 GHz); 35W Intel® Core™ i5-9500E (6 Cores, 9M Cache, up to 4.2 GHz); 65W Intel® Core™ i5-9500TE (6 Cores, 9M Cache, up to 3.6 GHz); 35W Intel® Core™ i3-9100E (4 Cores, 6M Cache, 3.7 GHz); 65W Intel® Core™ i3-9100TE (4 Cores, 6M Cache, to 3.2 GHz); 35W	
	Chipset	Intel® H310/Q370	
	Memory	Q370 : Four 288-pin DIMM up to 128GB Dual Channel DDR4 2400/2666 MHz H310 : Two 288-pin DIMM up to 64GB Dual Channel DDR4 2400/2666 MHz	
	BIOS	AMI SPI 128Mbit	
	Controller	Intel® HD Gen 9 Graphics	
GRAPHICS	Feature	OpenGL 5.0, DirectX 12, OpenCL 2.1 HW Decode: AVC/H.264, MPEG2, VC1/WMV9, JPEG/MJPEG, HEVC/H265, VP8, VP9 HW Encode: MPEG2, AVC/H264, JPEG, HEVC/H265, VP8, VP9	
	Display	1 x VGA 1 x DVI-I (DVI-D signal) 1 x DP++	VGA: resolution up to 1920x1200@60Hz DVI-D: resolution up to 1920x1200@60Hz DP++: resolution up to 4096x2160@60Hz
	Dual Displays	H310: VGA & DVI-D / VGA & DP++ / DP++ & DVI-D	
	Triple Displays	Q370: VGA & DVI-D & DP++	
	External	1 or 2 x 3.5"/2.5" SATA 3.0 drive bays (1 x 3.5" SATA drive bay, by default) 1 x 5.25" Optical drive bay	
STORAGE	Internal	1 x mSATA	
	Interface	CS330-Q370 : 1 x PCIe x16 (Gen 3) 1 x PCIe x4 (Gen 3) 2 x PCI 1 x Full-size Mini PCIe (USB/PCIe/mSATA, PCIe by default) CS330-H310 : 1 x PCIe x16 (Gen 3) 1 x PCIe x4 (Gen 2) 2 x PCI	
	Audio Codec	Realtek ALC888	
AUDIO	Interface	1 x Line-out 1 x Mic-in 1 x Line-in (opt.)	
	Controller	1 x Intel® I211AT (10/100/1000Mbps) 1 x Intel® I219V (10/100/1000Mbps)	
ETHERNET	Indicators	1 x Power LED 1 x HDD LED	
LED	Ethernet	2 x GbE (RJ-45)	
	Serial	1 x RS-232/422/485 (RS-232 w/ power) (DB-9)	
	USB	4 x USB 3.1 Gen 1 2 x USB 2.0	
	Display	1 x VGA 1 x DVI-I (DVI-D signal) 1 x DP++	
	Audio	1 x Line-out 1 x Mic-in 1 x Line-in (opt.)	
	PS/2	1 x PS/2 (mini-DIN-6)	
	Buttons	1 x Power button 1 x Reset button	
	Output & Interval	System Reset, Programmable via Software from 1 to 255 Seconds	
WATCHDOG TIMER	TPM	Infineon TPM1.2/2.0 (optional)	
SECURITY	Supply	Flex ATX 150W/250W/350W/400W/500W (250W Default)	
POWER	Fan	1 x 12cm System Fan	
COOLING			

SPECIFICATION

OS SUPPORT	Windows	Windows 10
	Linux	Linux
ENVIRONMENT	Operating Temperature	0 to 45°C
	Storage Temperature	0 to 60°C
	Relative Humidity	5 to 95% RH (non-condensing)
MECHANICAL	Construction	Sheet metal
	Mounting	Wall mount
	Dimensions(W x H x D)	349mm x 140.2mm x 290.9mm (13.74" x 5.52" x 11.45")
	Weight	7.7kg
STANDARDS AND CERTIFICATIONS	Color	no coating or black coating
	Shock	Operating: 3G Non-operating: 5G
	Vibration	Operating: Random 5~500Hz 0.5G Non-operating: Sine 10~500Hz 1.5G
	Package Drop	ISTA Project 1A
	Certification	CE, FCC Class A, RoHS

ORDERING INFORMATION

Model Name	Part Number	Description
WM343-CS330	750-WM3436-000G	WM343-CS, uATX System, Black, CS330-H310, 250W, F/G SYSTEM RoHS
WM343-CS330	750-WM3436-100G	WM343-CS, uATX System, Black, CS330-Q370, 250W, F/G SYSTEM RoHS

OPTIONAL ITEMS

Optional Items	Part Number	Description
CPU	TBD	CPU Intel Core i7/i5/i3/Pentium/Celeron CPU
Memory	TBD	4GB to 32GB, DDR4 U-DIMM RAM
mSATA SSD	TBD	8GB to 256GB, SATA MLC/TLC mSATA SSD
2.5" SSD	TBD	32GB to 1TB, SATA MLC/TLC 2.5" SSD
2.5" HDD	TBD	500GB to 2TB, SATA 2.5" HDD
3.5" HDD	TBD	500GB to 16TB, SATA 3.5" HDD
Power Cord	785-PWRD	Power Cord, Standards (USA/EUR/CH), 1.8m, RoHS for test only
Power Supply	TBD	AC/ATX FLEX 150W/250W/350W/400W/500W
Wall Mount	761-WM3410-000G	ACCESSORY WALL MOUNT KITS WM34x Series RoHS
Wall Mount	761-WM3410-000G	ACCESSORY WALL MOUNT KITS WM34x Series RoHS

PACKING LIST

1 WM343-CS330 System Unit
1 CPU cooler
1 SATA Data Cable (Length: 650mm)
4 HDD Screws
1 Quick Installation Guide
1 PSU Flex ATX 150W/250W/350W/400W/500W (250W Default)
1 System Fan