



## ARC-1535-B

15" Intel® Atom™ SoC Processor  
x6211E/x6413E/x6425E Fanless Rugged Touch  
Panel PC with IET Expansion

- > Onboard Intel® Atom™ Elkhart Lake x6211E/x6413E/x6425E Processor
- > Full Flat Front Panel with Projected Capacitive Touch Supports Multi Touch
- > One 260-pin SODIMM sockets supports up to 32GB DDR4 3200 SDRAM
- > 4 x USB3.2, 2 x COM
- > Dual Intel Gigabit LAN
- > 2 x M.2 Slots (Key-B 2242/3042/3052, Key-E 2230)
- > Support Wi-Fi / BT / 4G / 5G (by option)
- > Wide Voltage +12V ~ +24V Input, ErP Power
- > Available Expansion for Audio, USB, COM, HDMI, PCIe, GPIO, CAN Bus
- > IP65 Compliant Front Panel, IP41 Rear Box
- > With Panel Mount kits included
- > TPM 2.0 Function (Optional)
- > Fanless Operation Wide temp. from -20°C ~ 55°C (-4°F ~ 131°F)

### + Spec

System Information	
<b>Processor</b>	Onboard Intel® Elkhart Lake Processor Intel Atom® x6211E Processor (6W, 1.5M Cache, up to 3.00 GHz) Intel Atom® x6413E Processor (9W, 1.5M Cache, up to 3.00 GHz) Intel Atom® x6425E Processor (12W, 1.5M Cache, up to 3.00 GHz)
<b>System Memory</b>	1 x 260-pin DDR4 3200 MHz SO-DIMM socket, supports up to 32GB Max (In-BEND ECC supported)
<b>I/O Chipset</b>	EC ITE IT5571
<b>Watchdog Timer</b>	HW Reset, 1sec. ~ 65535min. and 1sec. or 1min./step
<b>H/W Status Monitor</b>	Monitoring CPU & System Temperature and Voltage
<b>SBC</b>	ARC-EHL
Expansion	
<b>Expansion</b>	1 x M.2 Key-B 2242/3042/3052 with SIM card slot Support SATA3 (BOM option for USB or PCIe for LTE(4/5G))  1 x M.2 Key-E 2230 Support PCIe/USB Wi-Fi/BT module  1 x 80-pin IET interface
Storage	
<b>Storage</b>	1 x 2.5" Drive Bay (7mm HDD Restricted)
Panel	
<b>LCD Size</b>	15", 4:3
<b>Display Type</b>	XGA
<b>Resolution</b>	1024 x 768
<b>Pixel pitch</b>	0.297mm(H) x 0.297mm(V)
<b>Luminance</b>	300 cd/m <sup>2</sup>
<b>Contrast ratio</b>	2000
<b>Viewing angle</b>	88 (U), 88 (D), 88 (L), 88 (R)
<b>Response time</b>	16 ms
<b>Backlight</b>	LED
<b>Touch Type</b>	Projective Capacitive Multi-Touch up to 10 points
<b>Touch Light Transmission</b>	89 %
<b>Touch Controller</b>	USB touch (ILITEK ILI2511, COF)
I/O	
<b>USB Port</b>	4 x USB 3.0
<b>COM Port</b>	1 x RS-232/422/485 1 x RS-232
<b>SATA</b>	1 x SATA III
<b>Other</b>	7 x Knockouts for Antenna Mounting *5 from rear cover + 2 from IET bracket
Display	
<b>Graphic Chipset</b>	Intel® Elkhart Lake SoC integrated Graphics Supports optional dual display
<b>Spec. &amp; Resolution</b>	HDMI: Max. resolution 4096x2160 @ 24Hz (Optional by IET module)
Audio	
<b>Audio Codec</b>	Realtek ALC888S(co-layout 897)
<b>Speaker Output</b>	2 x 2W
Certifications	
<b>Certification Information</b>	CE FCC Class B
Ethernet	



<b>LAN Chipset</b>	2 x Intel® I225-IT 2.5 Gigabit Ethernet
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ-45
<b>Power Requirement</b>	
<b>DC Input</b>	+12V ~ +24V
<b>DC Input Connector</b>	Lockable DC Jack
<b>Adapter</b>	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter
<b>Mechanical &amp; Environmental</b>	
<b>Operating Temperature</b>	Wide temp.-20°C ~ 55°C (-4°F ~ 131°F)
<b>Storage Temperature</b>	Wide temp.-30°C ~ 70°C(-22°F ~ 158°F)
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Weight</b>	3.7 Kgs
<b>Vibration Test</b>	With SSD/M.2 SSD : 3Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30mins/axis
<b>Shock Test</b>	Operating with SSD/M.2 : MIL-STD-810G, Method 516.6, Procedure I, functional shock=20G
<b>IP Rating</b>	Front IP65 Rear IP41
<b>Mounting Kit</b>	Wall / Stand / VESA 75mm x 75mm, 100mm x 100mm Panel Mount with mounting kits
<b>Power Mode</b>	AT/ATX (ATX is default setting)
<b>System Fan</b>	Fanless
<b>Construction - Front</b>	Die Casting with Cover lens
<b>Construction - Rear</b>	Black Die Casting
<b>Dimension</b>	350.51 x 274.51 x 56.5 mm
<b>Software Support</b>	
<b>OS Information</b>	Win10 / Linux
<b>Ordering Information</b>	
<b>Ordering Information</b>	<p>ARC-1535-X13-B1-1R 15" 1024x768 Industrial Touch Panel PC, ErP Design, PCAP Multi Touch(ALC888S) Intel Atom SoC x6413E 1.50 GHz CPU/2GLAN/2COM/4USB/SPK/12~24V input/12V Adapter</p> <p>Optional IET Module list:</p> <p>ACC-ARC-USB-01R 4 x USB 3.0 IET module for ARC-1535/38</p> <p>ACC-ARC-AUDIO-01R HDMI + 5.1 CH audio IET module for ARC-1535/38</p> <p>ACC-ARC-MPCIE-02R HDMI + MPCIE w/SIM IET module for ARC-1535/38</p> <p>ACC-ARC-COM-01R 2 x Isolated RS-232 IET module for ARC-1535/38</p> <p>ACC-ARC-COM-02R 3 x RS-232 IET module for ARC-1535/38</p> <p>ACC-ARC-COM-03R 2 x RS-232 + USB IET module for ARC-1535/38</p> <p>ACC-ARC-COM-04R 2 x RS-232 + LAN IET module for ARC-1535/38</p> <p>ACC-ARC-GPIO-01R 12-bit GPIO + 2-pin CAN bus IET module for ARC-1535/38</p> <p>ACC-ARC-OBDI-01R OBDI - CAN bus IET module for ARC-1535/38 (OBDI/EOBD for small vehicle)</p> <p>ACC-ARC-OBDI-02R OBDI - CAN bus IET module for ARC-1535/38 (J1939/J1708 for large vehicle)</p> <p>ACC-ARC-OBDI-03R OBDI - CAN bus IET module for ARC-1535/38 (ISO15765-4 for special large vehicle)</p> <p>E1702031800R Australia Power Cord</p> <p>E1702031835R USA Power Cord</p> <p>E170203183BR Japan Power Cord</p> <p>E170203183ER UK Power Cord</p> <p>E170203183DR EU Power Cord</p>