# KS070-M8M



#### **KEY FEATURES**



#### 7" 1024x600 TFT LCD Panel

with capacitive touch screen



## **High Speed LPDDR4**

2GB/4GB SDRAM Memory Down

NXP i.MX8M

## NXP i.MX8M Platform

performance up to 30% enhancement



### **Multiple Expansion**


M.2 2230/3042 support





#### **IP65**

IP65 front panel protection

#### **DIMENSIONS**







214.60

### **SPECIFICATION**

SYSTEM	Processor	NXP i.MX 8M Dual Cortex-A53, 1.3GHz		
	Memory	2GB/4GB SDRAM Memory Down Single Channel LPDDR4 1600MHz		
DISPLAY AND	Display	7" 1024x600 TFT LCD Panel with Capacitive Touch Screen		
TOUCH SCREEN	Brightness	425 cd/m <sup>2</sup>		
	Contrast	800:1		
	Backlight Lifetime	50,000 hours		
STORAGE	Internal	16GB eMMC		
		1 x Internal Micro SD Socket		
EXPANSION	Interface	1 x M.2 B key 3042/2242 (USB 2.0) 1 x M.2 E key 2230 (PCle x1/USB 2.0) 1 x Nano SIM slot (Optional)		
LED	Indicators	1 x Power LED		
TOP I/O	Wi-Fi Antenna	2 x Wi-Fi Module Antenna Hole		
BOTTOM I/O	Ethernet	1 x GbE (RJ-45)		
	Serial	1 x RS-232/422/485 1 x RS-485		
	USB	2 x USB 3.1 (type A)		
	Buttons	1 x Power Switch		
	Audio	1 x Line out		
	DIO	1 x 8-bit DIO		
INTERNAL I/O		1 x micro USB Type B		
WATCHDOG TIMER	Output & Interval	System Reset, Programmable via Software from 1 to 255 Seconds		
POWER	Туре	12V		
	Connector	2-Pole Terminal Block		
OS SUPPORT	OS Support	Android 9.0 & Yocto 4.3		
ENVIRONMENT	Operating Temperature	0 to 60°C -20~70°C by request		
	Storage Temperature	-30 to 85°C		
	Relative Humidity	85%@65°C (non-condensing)		
MECHANISM	Dimensions	235 x 150 x 43.8(W x H x D)		
	Construction	Aluminum front bezel		
	Mounting	Panel Mount /VESA Mount /Din-rail(Optional)		
	Weight	1.2kg		
STANDARDS AND CERTIFICATIONS	Shock	OP: Half-sine, 3G @ 11ms Non-OP: Half-sine, 5G @ 11ms		
	Vibration	OP: Random, 1Grms @ 5~500Hz, 30min Non-OP: Sweep sine, 3Grms @ 10~500Hz, 30min		
	Certifications	CE, FCC Class B		

## **ORDERING INFORMATION**

Model Name	Part Number	Description
KS070P-M8M	750-KS0703-000G	KS070P-M8M: M8M051, Fan-less 7" Panel PC; NXP i.MX 8M Dual Cortex-A53; 2GB DDR4; eMMC 16GB; PCT, Assy. RoHS
KS070P-M8M	750-KS0703-100G	KS070P-M8M: M8M051, Fan-less 7" Panel PC; NXP i.MX 8M Dual Cortex-A53; 4GB DDR4; eMMC 16GB; PCT, Assy. RoHS

### **PACKING LIST**

1 To	uch	Panel	PC
------	-----	-------	----

1 Poron foam

1 Quick Installation Guide