




ECM-SKLU

6th Gen Intel® Sky Lake-U Processor 3.5" Micro Module



- > Onboard 6th Gen Intel®Core™ i7/i5/i3 BGA Processor
- > One 260-pin DDR4 SODIMM Socket, Supports Up to 16GB DDR4 2133 SDRAM (only support non-ECC)
- > Triple Display, Dual-channel 18/24-bit LVDS, Dual HDMI
- > 1 SATA III, 1 Mini PCIe, 1 M.2 (2242) B-Key, 4 USB 3.0 (compatible with USB 2.0), 2 USB 2.0, 6 COM, 8-bit GPIO
- > HD Audio, Dual Gigabit Ethernet
- > TPM 2.0/1.2 (Both optional)

+ Spec

-System Information-	
Processor	6th Gen Intel® Core™ i7-6600U, 2-Core, 2.6GHz processor 6th Gen Intel® Core™ i5-6300U, 2-Core, 2.4GHz processor 6th Gen Intel® Core™ i3-6100U, 2-Core, 2.3GHz processor
System Memory	1 x 260-Pin DDR4 2133MHz SO-DIMM up to 16 GB
I/O Chipset	EC ITE IT8528E
BIOS Information	AMI uEFI BIOS, 128Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec.
H/W Status Monitor	Monitoring CPU Temperature, Voltage and FAN Status with Auto Throttling Control
Expansion	
Expansion	1 x Mini PCIe Supports mSATA 1 x M.2 (2242) B-Key with Micro SIM Card connector for 3G/4G
Storage	
Storage	1 x mSATA Supported from Mini PCIe 1 x M.2 support SATA or PCIe1/USB
I/O	
USB Port	2 x USB 2.0 4 x USB 3.0
COM Port	1 x RS-232/422/485 5 x RS-232
SATA	1 x SATA III
DIO	1 x 8bit GPIO
MIO	1 x LPC 1 x SPI
Other	1 x SIM Card Slot
Display	
Graphic Chipset	Intel® Skylake U SoC integrated Graphics Supports triple display
Spec. & Resolution	HDMI: Max. resolution 4096x2160 @ 24Hz LVDS: Max. resolution 1920x1080@ 60Hz LVDS + Dual HDMI Dual-channel 18/ 24-bit LVDS
Audio	
Audio Codec	Realtek ALC888S supports 5.1-CH
Certifications	
Certification Information	CE FCC Class B
Ethernet	
LAN Chipset	1 x Intel® I210AT 1 x Intel® I219LM
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Mechanical & Environmental	
Operating Temperature	0°C ~ 60°C (32°F ~ 140°F)
Storage Temperature	-40°C ~ 75°C (-40°F ~ 167°F)
Operating Humidity	40°C @ 95% Relative Humidity, Non-condensing
Weight	0.44lbs (0.2kg)
Power Requirement	+12V ~ +24V
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI 5.0 Compliant
Power Mode	AT/ATX



Dimension (L x W)	5.7" x 4" (146mm x 101mm)
Software Support	
OS Information	Win 10 Win 8.1 Win 7 Linux
Ordering Information	
Ordering Information	ECM-SKLU-6300-B2R 3.5" W/i5 6300U/6USB/6COM/2LAN/B2