

CSB100-895

Slim Type System for IBASE IB895 3.5" Disk-Size SBC



Specifications

System Mainboard	IB895
CPU Type	Intel® Atom™ Processor D2550
System Speed	1.86GHz
Memory	1x 2GB DDR3-1333 SO-DIMM, Max. 4GB (Intel® Atom™ D2550)
Construction	Aluminum & Steel
Chassis Color	Black
Front Panel External I/O	4x USB 2.0 ports 1x Line-out, 1x Mic-in 1x Power LED, 1x HDD LED 1x Power on/off button, 1x Reset button
Rear Panel External I/O	2x USB 2.0 port 1x DVI-I connectors 2x DB9 for COM1 (RS232/422/485, select from BIOS) /COM2 2x RJ45 GbE connectors 1x DC jack
Storage	1x 2.5" HDD or SSD
Power Supply	60W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	113.6mm (W) x 172.4mm (D) x 52.4mm (H)
Operating Temperature	-0°C~45°C (32°F~113°F)
Storage Temperature	-20°C ~ 80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Operating : 0.25Grms / 5~500Hz Non-operating : 1Grms / 5~500Hz
Shock	Operating : 20G / 11ms Non-operating : 40G / 11ms
Certification	CE / LVD / FCC Class B / CCC

Features

- Fanless system supports IBASE IB895 3.5" Disk-Size SBC
- On board Intel® Atom™ Processor D2550, 1.86GHz
- iSMART- for auto-scheduler and power resume
- 6x USB 2.0 ports
- Supports 2x Mini PCI-E (1x full-size & 1x half size)
- Supports 1x 2.5" SATA HDD device
- Wall mount kit included
- 12V~24V DC wide range power input

Ordering Information

CSB100-895 Steel Chassis with IB895 3.5-inch Disk Size SBC, Intel® Atom™ D2550(1.86GHz), 1x 2GB DDR3 memory, 320GB 2.5" HDD, desktop stand & mounting brackets, 60W power adaptor (RoHS)

Dimensions and Drawing

