



## EPM-1502

### eDP to VGA converter

- > Support VESA and CEA timing standards up to 1920x1200@60Hz with reduced blanking
- > Compliant with Embedded DisplayPort (eDP) specification version 1.3
- > VGA output is compliant with VESA VSIS v1r2 specification
- > Support analog RGB output for VGA with Triple 9-bit DAC up to 200MHz pixel rate

#### + Spec

I/O	
<b>Input Interface</b>	40pin eDP
<b>Output Interface</b>	DB-15 VGA
Display	
<b>Spec. &amp; Resolution</b>	1920x1200@60Hz with reduced blanking
<b>Multiple Display</b>	Depend on the Intel platform
Mechanical & Environmental	
<b>Operating Temperature</b>	Standard temperature 0°C ~ 60°C Wide temperature -40°C ~ 85°C
<b>Storage Temperature</b>	-40°C ~ +85°C
<b>Weight</b>	11g
<b>Vibration Test</b>	5G @5~500Hz
<b>Dimension</b>	50mm*50mm*10.55mm
<b>Form-Factor</b>	Customizes
Ordering Information	
<b>Ordering Information</b>	Standard temp. ordering PN: -EPM-1502-A1R  Wide temp. ordering PN: -EPM-1502-A2R