

EMP2-X203

mPCIe to two RS232

Customer:

Customer

Part Number:

Innodisk

Part Number:

Innodisk

Model Name:

Date:

Innodisk	Customer
Approver	Approver

Total Solution For
Embedded Peripherals

Table of Contents

TABLE OF CONTENTS	I
REVISION HISTORY	II
LIST OF TABLES	1
LIST OF FIGURES	2
1. PRODUCT INTRODUCTION	3
1.1. OVERVIEW	3
1.2. FEATURES	3
2. PRODUCT SPECIFICATIONS	4
2.1. DEVICE PARAMETERS	4
2.2. PERFORMANCE	4
2.3. ELECTRICAL SPECIFICATIONS	5
2.3.1. POWER REQUIREMENT	5
2.3.2. POWER CONSUMPTION	5
2.4. ENVIRONMENTAL SPECIFICATIONS	5
2.4.1. TEMPERATURE RANGES	5
2.4.2. HUMIDITY	5
2.4.3. SHOCK AND VIBRATION	5
2.4.4. MEAN TIME BETWEEN FAILURE (MTBF)	6
2.5. CE AND FCC COMPATIBILITY	6
2.6. ROHS COMPLIANCE	6
2.7. HARDWARE	6
2.7.1. LAYOUT	6
2.7.2. PIN DEFINE	7
2.7.3. I/O CONNECTOR MECHANICAL DRAWING & PIN DEFINES	8
2.7.4. EMP2-X203 MECHANICAL DRAWING	9
2.7.5. CABLE MECHANICAL DRAWING & PIN DEFINES	9
2.7.6. PACKING LIST	10
2.8. SOFTWARE SUPPORT	10
3. INSTALLATION GUIDE	10
4. APPEDIX	11
CONTACT US	15

REVISION HISTORY

Revision	Description	Date
1.0	First Released	Aug, 2018
1.1	mPCIe Pin Define 3.3V => 3.3V AUX	Mar, 2020

List of Tables

TABLE 1: DEVICE PARAMETERS	4
TABLE 2: RS232 PERFORMANCE (UNIT: SECOND).....	4
TABLE 3: POWER REQUIREMENT.....	5
TABLE 4: POWER CONSUMPTION	5
TABLE 5: TEMPERATURE RANGES.....	5
TABLE 6: SHOCK AND VIBRATION	5
TABLE 7: MEAN TIME BETWEEN FAILURE (MTBF).....	6
TABLE 8: PCB LAYOUT LEGEND.....	7
TABLE 9: MPCIe PIN DEFINE	7
TABLE 10: WIRE TO BOARD SMD 2*10P CONNECTOR PIN DEFINE (CN3)	8
TABLE 11: DB9 CABLE PIN DEFINE	10

List of Figures

FIGURE 1: BLOCK DIAGRAM	3
FIGURE 2: PICTURE	4
FIGURE 3: WIRE TO BOARD SMD 2*10P CONNECTOR DRAWING (CN3)	8
FIGURE 4: EMP2-X203 DRAWING	9
FIGURE 5: DB9 CABLE DRAWING	9

1. Product Introduction

1.1. Overview

Innodisk EMP2-X203 is designed with standard Mini PCI Express form factor, EMP2-X203 supports PCIe Gen 2.0 with a single lane to two independent UARTs RS232, optimized for higher performance and lower power, which brings you a flexible expansion solution for embedded systems.




Figure 1: Block Diagram

1.2. Features

- PCI-Express specification Rev. 2.0 compliant
- Up to 1 Mbps serial data rate. 16550 compatible. 256-byte FIFOs
- Industrial temperature (-40 °C to 85 °C) operation
- Flexible design with DB-9 connectors and cable
- ESD up to 15KV(Electrostatic Discharge) protection circuit to prevent system damage
- Supports CTS/RTS hardware flow control




Figure 2: Picture

2. Product Specifications

2.1. Device Parameters

Table 1: Device Parameters

Form Factor	mPCIe
Input I/F	PCI Express 2.0 x 1
Output I/F	RS-232
Output Connector	DB-9 x 2
Dimension (WxLxH)	30 x 50.9 x 6.7 mm

2.2. Performance

Table 2: RS232 Performance (unit: second)

Baud Rate	Transmission Data Size	RS232
		10m
9600	5Kbyte	5
	1Mbyte	1,266
115200	1Mbyte	105
460800	1Mbyte	26
921600	1Mbyte	13

2.3. Electrical Specifications

2.3.1. Power Requirement

Table 3: Power Requirement

Item	Connector	Rating
Input voltage	mPCIe Golden Finger	+3.3 DC +-5%

2.3.2. Power Consumption

Table 4: Power Consumption

Full Load (mA)	Voltage (V)
135	3.3

2.4. Environmental Specifications

2.4.1. Temperature Ranges

Table 5: Temperature Ranges

Temperature	Range
Operating	Industrial Grade: -40°C to +85°
Storage	-55°C to +95°

2.4.2. Humidity

Relative Humidity: 10-95%, non-condensing

2.4.3. Shock and Vibration

Table 6: Shock and Vibration

Reliability	Test Conditions	Reference Standards
Vibration	7 Hz to 2K Hz, 20G, 3 axes	IEC 68-2-6
Mechanical Shock	Duration: 0.5ms, 1500 G, 3 axes	IEC 68-2-27

2.4.4. Mean Time between Failure (MTBF)

Reliability prediction methodology provides the basis for reliability evaluation and analysis. The purpose of the prediction is to predict the life time of the product in units of failure rate and MTBF.

Table 7: Mean Time between Failure (MTBF)

Product	Condition	MTBF (Hours)
EMP2-X203	The analysis is at 25°C ambient temperature by Telcordia SR-332, Issues 4, Method I, Case 3 under Ground Benign, Controlled environment, 50% operation stress	TBD

2.5. CE and FCC Compatibility

EMP2-X203 conforms to CE and FCC requirements.

2.6. RoHS Compliance

EMP2-X203 is fully compliant with RoHS directive.

2.7. Hardware

2.7.1. Layout




Table 8: PCB Layout Legend

Label	Connector Type	Function
CN3	Wire to board SMD 2*10P 180° P:1.25mm H:4.8mm	RS232 Port 1(red edge cable), 2

2.7.2. Pin Define**Table 9: mPCIe Pin Define**

Signal Name	Pin #	Pin #	Signal Name
NC	51	52	3.3V AUX
NC	49	50	GND
NC	47	48	NC
NC	45	46	NC
GND	43	44	NC
3.3V AUX	41	42	NC
3.3V AUX	39	40	GND
GND	37	38	NC
GND	35	36	NC
PERXP	33	34	GND
PERXN	31	32	NC
GND	29	30	NC
GND	27	28	NC
PETXP	25	26	GND
PETXN	23	24	3.3V AUX
GND	21	22	PERST#
NC	19	20	NC
NC	17	18	GND
GND	15	16	NC
REFCLK+	13	14	NC
REFCLK-	11	12	NC
GND	9	10	NC
CLKREQ#	7	8	NC

NC	5	6	NC
NC	3	4	GND
WAKE #	1	2	3.3V AUX

2.7.3. I/O Connector Mechanical Drawing & Pin Defines




Figure 3: Wire to Board SMD 2*10P Connector Drawing (CN3)

Table 10: Wire to Board SMD 2*10P Connector Pin Define (CN3)

Signal Name	Pin #	Pin #	Signal Name
CD_P2	2	1	CD_P1
RX_P2	4	3	RX_P1
TX_P2	6	5	TX_P1
DTR_21	8	7	DTR_P1
GND	10	9	GND
DSR_P2	12	11	DSR_P1
RTS_P2	14	13	RTS_P1
CTS_P2	16	15	CTS_P1
RI_P2	18	17	RI_P1
NC	20	19	NC

2.7.4. EMP2-X203 Mechanical Drawing




Figure 4: EMP2-X203 Drawing

2.7.5. Cable Mechanical Drawing & Pin defines




Figure 5: DB9 Cable Drawing

Table 11: DB9 Cable Pin Define

Pin #	1	2	3	4	5	6	7	8	9
Signal Name	CD	RXD	TXD	DTR	GND	DSR	RTS	CTS	RI

2.7.6. Packing List

- EMP2-X203 x1
- DB9 Cable x1

2.8. Software Support

- Windows: XP, Windows 7, 8 , 8.1, 10, WES7, CE7.0
- Linux: Kernel 2.6.x and above.(Linux source code for modification)

3. Installation Guide

Please download driver and user manual from Myinnodisk web site.
<https://myinnodisk.innodisk.com/myinnodisk/Login.aspx>

4. Appedix

innodisk

宜鼎國際股份有限公司 Innodisk Corporation

Tel:(02)7703-3000 Fax:(02) 7703-3555 Internet: <http://www.innodisk.com/>

REACH Declaration of Conformity

Manufacturer Product: All Innodisk EP products

1. 宜鼎國際股份有限公司（以下稱本公司）特此保證此售予貴公司之產品，皆符合歐盟化學品法案(Registration, Evaluation and Authorization of Chemicals; REACH)之規定

(<http://www.echa.europa.eu/de/candidate-list-table> last updated: 15/01/2018)。所提供之產品包含：(1) 產品或產品所使用到的所有原物料；(2) 包裝材料；(3) 設計、生產及重工過程中所使用到的所有原物料。

We Innodisk Corporation hereby declare that our products are in compliance with the requirements according to the REACH Regulation

(<http://www.echa.europa.eu/de/candidate-list-table> last updated: 15/01/2018).

Products include: 1) Product and raw material used by the product; 2) Packaging material; 3) Raw material used in the process of design, production and rework

2. 本公司同意因本保證書或與本保證書相關事宜有所爭議時，雙方宜友好協商，達成協議。

InnoDisk Corporation agrees that both parties shall settle any dispute arising from or in connection with this Declaration of Conformity by friendly negotiations.

立 保 證 書 人 (Guarantor)

Company name 公司名稱: InnoDisk Corporation 宜鼎國際股份有限公司

Company Representative 公司代表人: Randy Chien 簡川勝

Company Representative Title 公司代表人職稱: Chairman 董事長

Date 日期: 2018 / 02 / 08



宜鼎國際股份有限公司 Innodisk Corporation

Tel:(02)7703-3000 Fax:(02) 7703-3555 Internet: <http://www.innodisk.com/>

RoHS 自我宣告書 (RoHS Declaration of Conformity)

Manufacturer Product: All Innodisk EP products

- 一、 宜鼎國際股份有限公司（以下稱本公司）特此保證售予貴公司之所有產品，皆符合歐盟 2011/65/EU 及 (EU) 2015/863 關於 RoHS 之規範要求。

Innodisk Corporation declares that all products sold to the company, are complied with European Union RoHS Directive (2011/65/EU) and (EU) 2015/863 requirement.

- 二、 本公司同意因本保證書或與本保證書相關事宜有所爭議時，雙方宜友好協商，達成協議。

Innodisk Corporation agrees that both parties shall settle any dispute arising from or in connection with this Declaration of Conformity by friendly negotiations.

Name of hazardous substance	Limited of RoHS ppm (mg/kg)
鉛 (Pb)	< 1000 ppm
汞 (Hg)	< 1000 ppm
鎘 (Cd)	< 100 ppm
六價鉻 (Cr 6+)	< 1000 ppm
多溴聯苯 (PBBs)	< 1000 ppm
多溴二苯醚 (PBDEs)	< 1000 ppm
鄰苯二甲酸二(2-乙基己基)酯 (DEHP)	< 1000 ppm
鄰苯二甲酸丁酯苯甲酯 (BBP)	< 1000 ppm
鄰苯二甲酸二丁酯 (DBP)	< 1000 ppm
鄰苯二甲酸二異丁酯 (DIBP)	< 1000 ppm

立 保 證 書 人 (Guarantor)

Company name 公司名稱： Innodisk Corporation 宜鼎國際股份有限公司

Company Representative 公司代表人： Randy Chien 簡川勝

Company Representative Title 公司代表人職稱： Chairman 董事長

Date 日期： 2018 / 02 / 08



Certificate

Issue Date: November 7, 2016

Ref. Report No. ISL-16LE498CE

Product Name : mPCIe to four RS-232 module
 Models : E%P2-X#03
 (%: Form factor: (2: 2.5"SSD, 3:DDR3 DIMM, D:Dongle, G:NGFF_M.2, H:mPCIe Half, L:PCIe Low profile, M:mPCIe, S:SATA, X:Multi, Z:Others)
 #: Output items: (1:1Port, 2:2Ports, 3:3Ports, 4:4Ports, A~Z:TBD,X:Multi))
 Responsible Party : Innodisk Corporation
 Address : 5F., No.237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

We, International Standards Laboratory, hereby certify that:

The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in European Council Directive- EMC Directive 2014/30/EU. The device was passed the test performed according to :



Standards:

EN 55032:2015 and CISPR 32:2015
 AS/NZS CISPR 32:2015
 EN 61000-3-2:2014 and IEC 61000-3-2:2014
 EN 61000-3-3: 2013 and IEC 61000-3-3: 2013
 EN 55024: 2010+A1:2015 and CISPR 24: 2010+A1:2015
 EN 61000-4-2: 2009 and IEC 61000-4-2: 2008
 EN 61000-4-3: 2006+A1: 2008 +A2: 2010 and IEC 61000-4-3:2006+A1: 2007+A2: 2010
 EN 61000-4-4:2012 and IEC 61000-4-4:2012

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

International Standards Laboratory

W.H. Chang / Director

☐ Hsi-Chih LAB:

No. 65, Gu Dai Keng Street, Hsi-Chih Dist.,
 New Taipei City 221, Taiwan
 Tel: 886-2-2646-2550; Fax: 886-2-2646-4641



☒ Lung-Tan LAB:

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
 Tao Yuan City 325, Taiwan
 Tel: 886-3-407-1718; Fax: 886-3-407-1738



Certificate

Issue Date: November 7, 2016

Ref. Report No. ISL-16LE498FE

Product Name : mPCIe to four RS-232 module
 Model : E%P2-X#03
 (%: Form factor: (2: 2.5"SSD, 3:DDR3 DIMM, D:Dongle, G:NGFF M.2, H:mPCIe Half, L:PCIe Low profile, M:mFCIe, S:SATA, X:Multi, Z:Others)
 #: Output items: (1:1Port, 2:2Ports, 3:3Ports, 4:4Ports, A~Z:TBD,X:Multi))
 Applicant : Innodisk Corporation
 Address : 5F., No.237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

We, **International Standards Laboratory**, hereby certify that:

The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified. (refer to Test Report if any modifications were made for compliance).



Standards:

FCC CFR Title 47 Part 15 Subpart B: 2015- Section 15.107 and 15.109
 ANSI C63.4-2014
 Industry Canada Interference-Causing Equipment Standard ICES-003 Issue 6: 2016
 Class B

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

International Standards Laboratory

W.H. Chang

W.H. Chang / Director


☐ Hsi-Chih LAB:

No. 65, Gu Dai Keng Street, Hsi-Chih Dist.,
 New Taipei City 221, Taiwan
 Tel: 886-2-2646-2550; Fax: 886-2-2646-4641



☒ Lung-Tan LAB:

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
 Tao Yuan City 325, Taiwan
 Tel: 886-3-407-1718; Fax: 886-3-407-1738



Contact us

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

Tel: +886-2-77033000

Email: sales@innodisk.com

Branch Offices:

USA

usasales@innodisk.com

+1-510-770-9421

Europe

eusales@innodisk.com

+31-40-3045-400

Japan

jpsales@innodisk.com

+81-3-6667-0161

China

sales_cn@innodisk.com

+86-755-2167-3689

www.innodisk.com

© 2018 Innodisk Corporation.

All right reserved. Specifications are subject to change without prior notice.

July 1, 2020