

NUC-RPU

13th Generation Intel® Raptor Lake-U Fanless Ultra Slim System



Product Features

- 13th Gen Intel® Core™ i7/i5/i3 (15W) Processors
- 1-Memory Socket (Capacity Max. Up to 32GB DDR5 4800)
- 2-Intel® Ethernet Controller (1GbE, 2.5GbE)
- 3-Expanslot Slot (M.2 Key-E, Key-B, Key-M)
- 8-USB Port (2-USB 2.0, 4-USB 3.2 Gen 2x1, 2-USB 3.0)
- Support dTPM 2.0, iAMT
- Intel® Iris® Xe/ UHD Graphics
- 2-COM Port (RS-232/422/485)
- 2-Audio Jack (Mic-In, Line-Out)
- 4-Display (HDMI 2.0b)
- Support Table Stand, VESA, DIN Rail mount

Specification

System Information

Processor	Embedded (15W) Intel® Core™ i7-1365UE Processor Intel® Core™ i5-1345UE Processor Intel® Core™ i5-1335UE Processor Intel® Core™ i3-1315UE Processor Non-Embedded (15W) Intel® Core™ i7-1355U Processor Intel® Core™ i5-1335U Processor Intel® Core™ i3-1315U Processor
System Memory	1 x 262-Pin SO-DIMM Socket (Capacity Max. Up to 32GB DDR5 4800)
BIOS Information	AMI uEFI BIOS, 256Mbit SPI Flash ROM
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec
H/W Status Monitor	Monitoring CPU Temperature, Voltage with Auto Throttling Control
TPM	TPM 2.0
iAMT	Above Core i5 (selected SKUs)
SBC	NUC-RPU

Expansion

M.2	1 x M.2 Key-E 2230 (PCIe, USB 2.0, CNVi) 1 x M.2 Key-B 2242/3042/3052 with internal SIM slot (PCIe, SATA, USB 3.0, USB 2.0) 1 x M.2 Key-M 2280 (PCIe4x4)
------------	--

Storage

M.2	1 x M.2 Key-M 2280 NVMe (PCIe Gen4x4) 1 x M.2 Key-B 2242 SSD (SATA Gen3)
------------	---

Front I/O

USB	2 x USB 2.0
Power Button	1 x Power Button with LED
COM Port	2 x RS-232/422/485 (Control by BIOS setting)
LED Indicator	1 x Storage LED (Yellow) 1 x LTE LED (Green) 1 x Wi-Fi LED (Green)
Audio	1 x Mic-In 1 x Line-Out

Rear I/O

USB	4 x USB 3.2 Gen 2x1 2 x USB 3.2 Gen1
LAN Port	2-Intel® Ethernet Controller (1GbE, 2.5GbE)
HDMI	4 x HDMI 2.0b
AC/DC Input	1 x Lockable DC Jack

Right I/O

Antenna	2 x Covered antenna hole
----------------	--------------------------

Left I/O

Antenna	2 x Covered antenna hole
----------------	--------------------------

Display

Graphic Chipset	Intel® 13th Gen CPU integrated
Resolution	HDMI 2.0 4096x2304@60Hz

Audio

Audio Codec	RealTek ALC888S
--------------------	-----------------

Ethernet

LAN Chipset	1 x Intel® Ethernet Connection I219-LM 1 x Intel® Ethernet Controller I226-V
--------------------	---

Power Requirement

Adapter	AC to DC adapter
ACPI	Single power ATX support S0, S3, S4, S5
Power Mode	AT/ATX (ATX default)
Voltage Input Spec.	+12Vdc

Software Support

OS Win10, Win11, Linux

Certification

Certification Information CE FCC Class B

Mechanical & Environmental

Operating Temp. 0°C ~ 50°C (32°F ~ 122°F)

Storage Temp. -30~70C° (-22°F ~ 158°F)

Operating Humidity 40°C @ 95% Relative Humidity, Non-condensing

Dimension (W x L x H) 170mm x 125mm x 36mm(6.69" x 4.92" x 1.42")

Weight 0.85kg

Vibration Test With SSD: 1.5 Grms, IEC60068-2-64, Random, 5~500 Hz, 30 min/axis

Shock Test With SSD: 55Grms, IEC 60068-2-27, IEC 60068-2-27, Half Sine, 11ms

Drop Test ISTA 2A, IEC-60068-2-32 Test:Ed

IP Rating IP40

Mounting Kit Table Stand/Din Rail/VESA

Kensington Lock 1 x Kensington Lock