


RX680R

12/13th Gen. Intel® Core™ i9/i7/i5/i3
Processor, LGA 1700 Socket, Micro ATX
Motherboard With Intel® R680E



Product Features

- LGA 1700 Socket Supports 12/13th Gen. Intel® Core™ i9/i7/i5/i3 Processors, (Max. TDP at 65W) with Intel® R680E Chipset
- 4 x DP++, 1 x LVDS Header
- 2 x RJ45, Intel® I225-LM/I226-LM 2.5 Gigabit Ethernet Controller
- 2 x M.2 M-Key 2242/2280/22110 NVMe, 1 x M.2 E-Key 2230
- ATX Power
- 4 x 288 Pin DDR5 Dual Channel U-DIMM Socket, Support Up to 128GB (ECC Memory Support by CPU)
- 1 x Gen 5 PCIe x16, 2 x Gen 4 PCIe x4, 1 x Gen 3 PCIe x4 Open Ended
- 1 x USB 3.2 Gen 2x2 Type C, 6 x USB 3.2 Gen 2, 2 x USB 3.2 Gen 2, 8 x USB 2.0
- 1 x RS-232/422/485, 5 x RS-232

Specification

System Information

Processor	LGA 1700 Socket Supports 12/13th Generation Intel® Core™ i9/i7/i5/i3 Processors (Max. TDP at 65W)
Platform Controller Hub	Intel® R680E Chipset
System Memory	4 x 288-Pin DDR5 4400MHz Dual Channel U-DIMM Socket Supports Up to 128GB (ECC Memory Support by CPU)
I/O Chipset	nuvoton NCT6126D
Watchdog Timer	H/W Reset, 5~255 Seconds/5~255 Minutes
BIOS	AMI uEFI BIOS, 256Mbit SPI Flash ROM
H/W Status Monitor	CPU Temperature Monitoring Voltages Monitoring CPU Fan Speed Control
TPM	infineon TPM 2.0
Board	Micro ATX

Expansion

Expansion	1 x Gen 5 PCIe x16 2 x Gen 4 PCIe x4 (x16 Physical Yellow) 1 x Gen 3 PCIe x4 Open Ended 1 x M.2 M-Key 2242/2280/22110 NVMe (Gen 4 PCIe x4 + SATA III) 1 x M.2 M-Key 2242/2280/22110 NVMe (Gen 3 PCIe x4 + SATA III) 1 x M.2 E-Key 2230 with CNVi Support (PCIe x1 + USB 2.0)
-----------	---

Display	
Graphic Chipset	Intel® 12/13th Generation CPU Integrated
Spec. & Resolution	4 x DP (DP1.4a): Max: 7680 x 4320@60Hz (2 x DP++:1920 x 1080@60Hz)
Multiple Display	Four Diaplay
LVDS	1 x LVDS Header 1 x eDP Header (Optional)

Audio	
Audio Codec	Realtek ALC888S HD Audio Decoding Controller
Audio Interface	Line-out, Mic-in
Audio Amplifier	2 x 3W 8Ω Amplifier

Ethernet	
LAN Chipset	2 x Intel® I225LM/I226LM 2.5 Gigabit Ethernet
LAN Port	2 x RJ45

Power Requirement	
Power Mode	AT/ATX (Default Setting: ATX)

Software Support	
OS	Windows 10, Windows 11, Linux

Certification	
Certification Information	CE, FCC Class B, RoHS Compliant

I/O	
USB	1 x USB 3.2 Gen2x2 Type C 6 x USB 3.2 Gen2x1 2 x USB 3.2 Gen2x1 by pin header 8 x USB 2.0 by pin header
COM Port	5 x RS-232 by pin header 1 x RS-232/422/485 by pin header
SATA	4 x SATA III
RAID	Support RAID 0, 1, 5, 10
DIO	1 x 8-bit GPIO
MIO	1 x PS/2 Header 1 x LPT Header

Mechanical & Environmental	
Operating Temp.	0°C ~ 60°C (32°F ~ 140°F)
Storage Temp.	-20°C ~ 80°C (-4°F ~ 176°F)
Operating Humidity	5% ~ 90% Relative Humidity, Non-condensing

Weight	1.45lbs (0.65kg)
Power Requirement	+12V/+5V/5VSB/+3.3V/-12V
Power Mode	AT/ATX (Default Setting: ATX)
Dimension (L x W)	9.6" x 9.6" (243.84mm x 243.84mm)

Ordering Information

Ordering Information	71882-1A LGA 1700 socket supports 12th/13th Gen Intel® Core™ i9/i7/i5/i3 Processors Micro ATX Motherboard with Intel® R680E PCH
----------------------	---