

EMPU-3201

mPCIe to dual USB 3.0 Module

Customer:

Customer

Part Number:

Innodisk

Part Number:

Innodisk

Model Name:

Date:

Innodisk	Customer
Approver	Approver

Total Solution For
Embedded Peripherals

Table of Contents

TABLE OF CONTENTS	I
REVISION HISTORY	II
LIST OF TABLES	1
LIST OF FIGURES	2
1. PRODUCT INTRODUCTION	3
1.1. OVERVIEW	3
1.2. FEATURES	3
2. PRODUCT SPECIFICATIONS	5
2.1. DEVICE PARAMETERS	5
2.2. ELECTRICAL SPECIFICATIONS.....	5
2.2.1.POWER REQUIREMENT.....	5
2.2.2.POWER CONSUMPTION	5
2.3. ENVIRONMENTAL SPECIFICATIONS	5
2.3.1.TEMPERATURE RANGES.....	5
2.3.2.HUMIDITY	6
2.3.3.SHOCK AND VIBRATION	6
2.3.4.MEAN TIME BETWEEN FAILURE (MTBF)	6
2.4. CE AND FCC COMPATIBILITY.....	6
2.5. RoHS COMPLIANCE	6
2.6. HARDWARE.....	7
2.6.1.LAYOUT.....	7
2.6.2.PIN DEFINE	8
2.6.3.I/O CONNECTOR MECHANICAL DRAWING & PIN DEFINES	9
2.6.4.EMPU-3201 MECHANICAL DRAWING	11
2.6.5.CABLE MECHANICAL DRAWING.....	11
2.6.6.PACKING LIST	12
2.7. SOFTWARE SUPPORT.....	12
2.8. APPLICATION NOTE	13
3. APPEDIX	14
CONTACT US	18

REVISION HISTORY

Revision	Description	Date
1.0	First Released	Sep, 2020

List of Tables

TABLE 1: DEVICE PARAMETERS	5
TABLE 2: POWER REQUIREMENT.....	5
TABLE 3: POWER CONSUMPTION	5
TABLE 4: TEMPERATURE RANGES.....	5
TABLE 5: SHOCK AND VIBRATION	6
TABLE 6: MEAN TIME BETWEEN FAILURE (MTBF).....	6
TABLE 7: mPCIe PCB LAYOUT LEGEND.....	7
TABLE 8: mPCIe PIN DEFINE	8
TABLE 9: DIP 2*10P CONNECTOR (CUT 1PIN) (CN2) PIN DEFINE	9
TABLE 10: 4 PIN HEADER (CN1) PIN DEFINE	10

List of Figures

FIGURE 1: BLOCK DIAGRAM	3
FIGURE 2: MPCIE BOARD PICTURE.....	4
FIGURE 3: 19PIN PITCH 2.0 CONNECTOR TO 2 USB 3.0 CABLE	4
FIGURE 4: 4PIN POWER CABLE	4
FIGURE 5: DIP 2*10P(CUT 1PIN) 90° P:2.0MM CONNECTOR DRAWING	9
FIGURE 6: 4 PIN HEADER P:2.0MM DRAWING	10
FIGURE 7: EMPU-3201 MPCIE BOARD DRAWING	11
FIGURE 8: 19PIN PITCH 2.0 CONNECTOR TO 2 USB CABLE DRAWING	11
FIGURE 9: 4 PIN HEADER PITCH 2.0 POWER CABLE DRAWING.....	12

1. Product Introduction

1.1. Overview

Innodisk EMPU-3201 is designed with standard Mini PCI Express form factor, EMPU-3201 supports PCIe Gen 2.0 with a single lane to two independent USB 3.0 ports. EMPU-3201 supports USB battery charging specification rev. 1.2 and compliant with xHCI 1.0, USB 3.0 rev 1.0 which brings you a flexible design for small form factor or embedded systems.




Figure 1: Block Diagram

1.2. Features

- Supports 2 USB 3.0 ports (share PCIe Gen2 x1 bandwidth).
- Compliant with PCI Express Base Specification Revision 2.0
- Compliant with Universal Serial Bus 3.0 Specification Revision 1.0
- Supports 2 USB 3.0 ports (share PCIe Gen2 x1 bandwidth).
- Complies with EN61000-4-2 (ESD) Air-15kV, Contact-8kV



Figure 2: mPCIe Board Picture



Figure 3: 19pin Pitch 2.0 Connector to 2 USB 3.0 Cable



Figure 4: 4pin Power Cable

2. Product Specifications

2.1. Device Parameters

Table 1: Device Parameters

Form Factor	mPCIe
Input I/F	PCI Express 2.0 x 1
Output I/F	USB 3.0 x 2
Output Connector	19 Pin Pitch 2.0 Connector
Dimension (WxLxH)	mPCIe Board: 30.0 x 50.9 x 8.45 mm

2.2. Electrical Specifications

2.2.1. Power Requirement

Table 2: Power Requirement

Item	Connector	Rating
Input voltage	mPCIe Golden Finger	+3.3 DC +-5%

2.2.2. Power Consumption

Table 3: Power Consumption

Full Load (mA)	Voltage (V)
270	3.3

2.3. Environmental Specifications

2.3.1. Temperature Ranges

Table 4: Temperature Ranges

Temperature	Range
Operating	Standard Grade: 0°C to +70°C Industrial Grade: -40°C to +85°
Storage	-55°C to +95°

2.3.2. Humidity

Relative Humidity: 10-95%, non-condensing

2.3.3. Shock and Vibration

Table 5: Shock and Vibration

Reliability	Test Conditions	Reference Standards
Vibration	7 Hz to 2K Hz, 20G, 3 axes	IEC 68-2-6
Mechanical Shock	Duration: 0.5ms, 1500 G, 3 axes	IEC 68-2-27

2.3.4. Mean Time between Failure (MTBF)

Reliability prediction methodology provides the basis for reliability evaluation and analysis. The purpose of the prediction is to predict the life time of the product in units of failure rate and MTBF.

Table 6: Mean Time between Failure (MTBF)

Product	Condition	MTBF (Hours)
EMPU-3201-C1	The analysis is at 25°C ambient temperature by Telcordia SR-332, Issues 4, Method I, Case 3 under Ground Benign, Controlled environment, 50% operation stress	17,657,551
EMPU-3201-W1	The analysis is at 25°C ambient temperature by Telcordia SR-332, Issues 4, Method I, Case 3 under Ground Benign, Controlled environment, 50% operation stress	26,020,380

2.4. CE and FCC Compatibility

EMPU-3201 conforms to CE and FCC requirements.

2.5. RoHS Compliance

EMPU-3201 is fully compliant with RoHS directive.

2.6. Hardware

2.6.1. Layout




Table 7: mPCIe PCB Layout Legend

Label	Connector Type	Function
CN1	4 Pin Header P:2.0mm	External 5V Power *Please note that only 200mA in each port if 4pin power cable is not connected.
CN2	DIP 2*10P(cut 1pin) 90° P:2.0mm	USB 3.0 Signal

2.6.2. Pin Define

Table 8: mPCIe Pin Define

Signal Name	Pin #	Pin #	Signal Name
NC	51	52	3.3V AUX
NC	49	50	GND
NC	47	48	NC
NC	45	46	NC
GND	43	44	NC
3.3V AUX	41	42	NC
3.3V AUX	39	40	GND
GND	37	38	NC
GND	35	36	NC
RX+	33	34	GND
RX-	31	32	NC
GND	29	30	NC
GND	27	28	NC
TX+	25	26	GND
TX-	23	24	3.3V AUX
GND	21	22	PERST#
NC	19	20	NC
NC	17	18	GND
GND	15	16	NC
CLK+	13	14	NC
CLK-	11	12	NC
GND	9	10	NC
CLK	7	8	NC
NC	5	6	NC
NC	3	4	GND
PE_WAKE_N	1	2	3.3V AUX

2.6.3. I/O Connector Mechanical Drawing & Pin Defines




Figure 5: DIP 2*10P(cut 1pin) 90° P:2.0mm Connector Drawing

Table 9: DIP 2*10P Connector (cut 1pin) (CN2) Pin Define

Signal Name	Pin #	Pin #	Signal Name
Vbus	1		
IntA_P1_SSRX-	2	19	Vbus
IntA_P1_SSRX+	3	18	IntA_P1_SSRX
GND	4	17	IntA_P2_SSRX+
IntA_P1_SSTX-	5	16	GND
IntA_P1_SSTX+	6	15	IntA_P2_SSTX
GND	7	14	IntA_P2_SSTX+
IntA_P1_D-	8	13	GND
IntA_P1_D+	9	12	IntA_P2_D-
	10	11	IntA_P2_D+




Figure 6: 4 Pin Header P:2.0mm Drawing

Table 10: 4 Pin Header (CN1) Pin Define

Signal Name	Pin #
5V	1
GND	2
GND	3
5V	4

2.6.4. EMPU-3201 Mechanical Drawing




Figure 7: EMPU-3201 mPCIe Board Drawing

2.6.5. Cable Mechanical Drawing




Figure 8: 19pin Pitch 2.0 Connector to 2 USB Cable Drawing




Figure 9: 4 Pin Header Pitch 2.0 Power Cable Drawing

2.6.6. Packing List

- EMPU-3201 mPCIe Board x 1
- 19pin Pitch 2.0 Connector to 2 USB Cable x 1
- 4pin Pitch 2.0 Power Cable x 1

2.7. Software Support

- Windows: XP(32bit), 7(32/64bit), 8/8.1(32/64 bit), 10(32/64bit)
- Linux: Kernel 2.6 above.
- After Win8 and Linux Kernel v2.6.31 supports built-in xHCI 1.0 driver.

2.8. Application Note

EMPU-3201 module doesn't support OC(Over Current) warning.

3. Appedix

innodisk

宜鼎國際股份有限公司 Innodisk Corporation REACH Declaration

Tel:(02)7703-3000 Fax:(02) 7703-3555 Internet: <https://www.innodisk.com/>

Innodisk Corporation pursues its social responsibility for global environmental preservation by committing to be compliant with REACH regulation (REGULATION (EC) No 1907/2006). We hereby confirm that the product(s) delivered to

Innodisk P/N	Description
All Innodisk EP Products	

- ☐ contain(s) **no** hazardous substances or constituents exceeding the defined threshold 0.1 % by weight in homogenous material if not otherwise specified, as described in the candidate list table currently including 209 substances and shown on the ECHA website (<http://echa.europa.eu/de/candidate-list-table>).
- ☒ contain(s) one or more hazardous substances or constituents exceeding 0.1 % by weight in homogenous material if not otherwise specified in candidate list table. Where the threshold value is exceeded, the substances in question are to be declared in accompanying Appendix A.
- ☒ Comply with REACH Annex XVII.

Guarantor

Company name 公司名稱： Innodisk Corporation 宜鼎國際股份有限公司

Company Representative 公司代表人： Randy Chien 簡川勝

Company Representative Title 公司代表人職稱： Chairman 董事長

Date 日期： 2020 / 07 / 01

RoHS 自我宣告書(RoHS Declaration of Conformity)

Manufacturer Products: All Innodisk EM FLASH, DRAM and EP products

- 一、 宜鼎國際股份有限公司（以下稱本公司）特此保證售予貴公司之所有產品，皆符合歐盟 2011/65/EU 及(EU) 2015/863 關於 RoHS 之規範要求。
Innodisk Corporation declares that all products sold to the company, are complied with European Union RoHS Directive (2011/65/EU) and (EU) 2015/863 requirement.
- 二、 本公司同意因本保證書或與本保證書相關事宜有所爭議時，雙方宜友好協商，達成協議。
Innodisk Corporation agrees that both parties shall settle any dispute arising from or in connection with this Declaration of Conformity by friendly negotiations.
- 三、 本公司聲明我們的產品符合 RoHS 指令的附件中(7a)、(7c-I)允許豁免。
We declare, our products permitted by the following exemptions specified in the Annex of the RoHS directive.
- ※ (7a) Lead in high melting temperature type solders(i.e. lead-based alloys containing 85% by weight or more lead).
- ※ (7C-I) Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectric devices, or in a glass or ceramic matrix compound.

Name of hazardous substance	Limited of RoHS ppm (mg/kg)
鉛 (Pb)	< 1000 ppm
汞 (Hg)	< 1000 ppm
鎘 (Cd)	< 100 ppm
六價鉻 (Cr 6+)	< 1000 ppm
多溴聯苯 (PBBs)	< 1000 ppm
多溴二苯醚 (PBDEs)	< 1000 ppm
鄰苯二甲酸二(2-乙基己基)酯 (DEHP)	< 1000 ppm
鄰苯二甲酸丁酯苯甲酯 (BBP)	< 1000 ppm
鄰苯二甲酸二丁酯 (DBP)	< 1000 ppm
鄰苯二甲酸二異丁酯 (DIBP)	< 1000 ppm


立 保 證 書 人 (Guarantor)

Company name 公司名稱: Innodisk Corporation 宜鼎國際股份有限公司

Company Representative 公司代表人: Randy Chien 簡川勝

Company Representative Title 公司代表人職稱: Chairman 董事長

Date 日期: 2020 / 03 / 03



Certificate

Issue Date: March 10, 2016
Ref. Report No. ISL-16LE105CE

Product Name : Mini PCIe to dual USB 3.0 Module
Model : E%PU-3201
(%: Form factor: (2:2.5"SSD, 3:DDR3 DIMM, D:Dongle, G:NGFF_M.2, H:mPCIe Half, L:PCIe Low profile, M:mPCIe, S:SATA, X:Multi, Z:Others))
Responsible Party : Innodisk Corporation
Address : 5F., No.237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan (R.O.C.)

We, **International Standards Laboratory**, hereby certify that:

The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in European Council Directive- EMC Directive 2004/108/EC (marketed before 2016/04/19) 2014/30/EU (marketed after 2016/04/20). The device was passed the test performed according to :



Standards:

EN 55022: 2010+AC2011 and CISPR 22: 2008 (modified)
EN 61000-3-2:2014 and IEC 61000-3-2:2014
EN 61000-3-3: 2013 and IEC 61000-3-3: 2013
EN 55024: 2010 and CISPR 24: 2010
EN 61000-4-2: 2009 and IEC 61000-4-2: 2008
EN 61000-4-3: 2006+A1: 2008 +A2: 2010 and
IEC 61000-4-3:2006+A1: 2007+A2: 2010
EN 61000-4-4:2012 and IEC 61000-4-4:2012

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

International Standards Laboratory

W.H. Chang

W.H. Chang / Director

☐ Hsi-Chih LAB:

No. 65, Gu Dai Keng Street, Hsi-Chih Dist.,
New Taipei City 221, Taiwan
Tel: 886-2-2646-2550; Fax: 886-2-2646-4641



☒ Lung-Tan LAB:

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan
Tel: 886-3-407-1718; Fax: 886-3-407-1738



Certificate

Issue Date: March 10, 2016
Ref. Report No. ISL-16LE105FB

Product Name : Mini PCIe to dual USB 3.0 Module
Model : E%PU-3201
(%: Form factor: (2:2.5"SSD, 3:DDR3 DIMM, D:Dongle,
G:NGFF_M.2, H:mPCIe Half, L:PCIe Low profile, M:mPCIe,
S:SATA, X:Multi, Z:Others))
Applicant : Innodisk Corporation
Address : 5F., No.237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221,
Taiwan (R.O.C.)

We, **International Standards Laboratory**, hereby certify that:

The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified. (refer to Test Report if any modifications were made for compliance).



Standards:

FCC CFR Title 47 Part 15 Subpart B: 2014- Section 15.107 and 15.109
ANSI C63.4-2014
Industry Canada Interference-Causing Equipment Standard ICES-003 Issue 6: 2016

Class B

I attest to the accuracy of data and all measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

International Standards Laboratory

W.H. Chang / Director

☐ Hsi-Chih LAB:

No. 65, Gu Dai Keng Street, Hsi-Chih Dist.,
New Taipei City 221, Taiwan
Tel: 886-2-2646-2550; Fax: 886-2-2646-4641



☒ Lung-Tan LAB:

No. 120, Lane 180, Hsin Ho Rd., Lung-Tan Dist.,
Tao Yuan City 325, Taiwan
Tel: 886-3-407-1718; Fax: 886-3407-1738



Contact us

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

Tel: +886-2-77033000

Email: sales@innodisk.com

Branch Offices:

USA

usasales@innodisk.com

+1-510-770-9421

Europe

eusales@innodisk.com

+31-40-3045-400

Japan

jpsales@innodisk.com

+81-3-6667-0161

China

sales_cn@innodisk.com

+86-755-2167-3689

www.innodisk.com

© 2020 Innodisk Corporation.

All right reserved. Specifications are subject to change without prior notice.

March 26, 2024