

MI1002

Mini-ITX Motherboard

14th Gen Intel® Core™ Ultra DT Processors (Meteor Lake-PS Platform)



Coming soon



Features

- 14th Gen Intel® Core™ Ultra processors (Meteor Lake-PS)
- 2x DDR5 SO-DIMM, Max. 64GB
- Supports HDMI, DisplayPort(DP++), 2x Type-C
- 1x Intel® I226LM 2.5G LAN, 1x Intel® I226V 2.5G LAN
- 4x USB 3.2 Type-A, 2x USB 3.2 Type-C, 4x USB 2.0, 4x COM, 2x SATA III
- 1x PCI-E (x4), 3x M.2 (M-Key + E-Key + B-Key)
- Supports 5G & watchdog timer, Digital I/O, iAMT (18), dTPM (2.0) / fTPM (2.0)

Specifications

CPU Socket	LGA1851
CPU	14th Gen Intel® Core™ Ultra Processor for 1-chip SoC socket
PCH	N/A
Memory	2x DDR5 SO-DIMM, Max. 64GB
BIOS	AMI
Watchdog Timer	256 levels
H/W Monitor	Yes
Storage Device Interface	M.2 (M2280 for NVMe)
Expansion Slots	1x PCI-E (x4)
Mini Type Slots	1x M.2 (M-Key, Type:2280, supports NVMe with PCI-E(4x) signal only) 1x M.2 (E-Key, Type:2230, supports CNVi) 1x M.2 (B-Key, Type:3052, supports 5G/LTE)
Graphics Controller	14th Gen Intel® Core™ Ultra Processor integrated Iris® 8Xe graphics
Video Output	HDMI, DisplayPort, 2x Type-C
Ethernet	Intel® I226LM as 1st LAN, I226V as 2nd LAN
I/O Chipset	Fintek F81964D-I on board
Serial Port	N/A
USB 2.0	4x USB 2.0 via pin-header
USB 3.X	6x USB 3.2 (4x Type-A+ 2x Type-C)
Serial ATA	2x SATA III
Audio	Intel® MTL-PS built-in HD audio controller + Realtek codec ALC888S-VD2-GR
TPM	dTPM / fTPM
Others	Digital I/O (4-in/4-out); RAID, iAMT (18)
Dimensions (L x W)	170mm x 170mm
Power Consumption	TBD
Operating Temperature	0°C ~ 60°C (32°F~140°F)
Storage Temperature	-20°C ~ 80°C (-4°F ~ 176°F)
Relative Humidity	90% (non-condensing @60°C)

Ordering Information

MI1002AF	LGA1851 Mini-ITX Motherboard w/ HDMI, DisplayPort, 2x Type-C, Dual 2.5GbE, 2x SATA, iAMT (18.0), dTPM (2.0) / fTPM (2.0)
----------	--

1

Single Board Computers

2

CPU Modules

3

Motherboards

4

CPU Cards