



QBiX Lite Series (Digital Signage Players)

QBiX-Lite-RPLA1360PH-A1

Compare
Now

Preliminary

Key Features

Industrial system with Intel® Core™ i7-1360P Processor/ Fan Design/ Dual Channel DDR5 up to 64GB/ 2 x HDMI/ 2 x DP/ 2 x USB type C

- System Size: 234W x 155D x 30H (mm)
- Intel® Core™ i7-1360P Processor
- Dual Channel DDR5, 2 x SO-DIMMs
- 2 x HDMI
- 2 x Display Ports
- 2 x 2.5GbE LAN Ports

SHARE



Add to Compare

Add to Inquiry

QBiX Lite Series (Digital Signage Players)

QBiX-Lite-RPLA1360PH-A1

Add to Compare

Add to Inquiry

Specification

Specification

Dimension | 234W x 155D x 30H (mm)

CPU | Intel® Core™ i7-1360P Processor
Intel® 7, 12 cores, 4P+8E, 16 threads, up to 5.0 GHz

Memory | 2 x DDR5 SO-DIMM sockets, Max. Capacity 64 GB
Support Dual Channel DDR5 5200 MHz memory modules

Ethernet | 2 x 2.5GbE LAN Ports (Intel® I226V and Intel® I226LM)

Graphics Support | Integrated Graphics Processor - Intel Iris Xe Graphics :
2 x HDMI 2.1
2 x DP 1.4 (8K)
1 x DP 1.4 (USB Type C (8K))

Compare Now

(4 independent display outputs)

Audio

Realtek® Audio Codec

Storage

1 x 2.5" HDD/SSD (SATA 6Gb/s)

Expansion-Slots

1 x 2280 M.2 M-Key (PCIe x2, SATA 6Gb/s)
1 x 2230 M.2 E-Key
1 x 3052 M.2 B-Key with SIM slot (Support 5G)

Front I/O

1 x USB type C (USB 3.2 Gen 2x1, DP Alt Mode & PD Out -30W)(-100W requests to use 250W adapter)
1 x USB type C (USB 3.2 Gen 2x1, PD input-100W)
4 x USB 3.2 Gen 2x1
2 x HDMI
2 x DP
2 x RJ45 LAN Ports
2 x USB 2.0
1 x HDD LED
1 x Power button with LED
2 x External Antenna Holes (Optional)

Rear I/O

1 x COM Port (RS-232)
2 x USB 2.0
1 x Headphone Jack
1 x Screw type DC Jack
2 x External Antenna Holes (Optional)

Side I/O

1 x External Antenna Hole (on each side)

TPM

Onboard TPM 2.0 security chip
INFINEON SLB9670VQ2.0

Power

+12V~24VDC (Adapter 19.5V/135W)

Order Information

6BQL1360AMR-SI (Box packing)

Compare
Now