

Device Selection Guide



Products	Peach-E73	Pitaya-E42	Pitaya-E29	Pitaya-E21	Mongosteem-E29	Mongosteem-E21
Active area	7.3"	4.2"	2.9"	2.13"	2.9"	2.13"
Resolution	800 x 480	400 x 300	128 x 196	122 x 250	128 x 196	122 x 250
Wireless	Wi-Fi / BLE	Wi-Fi / BLE	Wi-Fi / BLE	Wi-Fi / BLE	Wi-Fi / BLE	Wi-Fi / BLE
Connector	USB Type-C	USB Type-C	NA	NA	NA	NA
LED	2 colors	2 colors	3 colors	3 colors	3 colors	3 colors
Keys	Power / BLE / Reset	Power / BLE / Reset	Power / BLE / Reset / Programmable x1	Power / BLE / Reset / Programmable x1	Power / BLE / Reset / Programmable x1	Power / BLE / Reset / Programmable x1
Battery	AAAx6	AAAx6	AAAx2	AAAx2	AAAx2	AAAx2
Colors	BWRY	BWR	BWR	BWR	BW	BW
Image update time (25°C typ)	18 sec	18 sec	18 sec	18 sec	0.5 sec	0.5 sec
Best optic temperature range	15°C ~ 35°C	15°C ~ 35°C	15°C ~ 35°C	15°C ~ 35°C	0°C ~ 50°C	0°C ~ 50°C
Storage temperature	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C	-20°C ~ 60°C

Headquarters 威強電工業電腦 IEI Integration Corp.

No. 29, Zhongxing Rd., Xizhi Dist., New Taipei City 221, Taiwan
TEL : +886-2-86916798 / +886-2-26902098 FAX : +886-2-66160028
sales@ieiworld.com www.ieiworld.com

America IEI Technology USA Corp.

138 University Parkway, Pomona, CA 91768
TEL : +1-909-595-2819 FAX : +1-909-595-2816
sales@usa.ieiworld.com usa.ieiworld.com

China 威強電工業電腦 IEI Integration (Shanghai) Corp.

上海市闵行区莘庄工业区申富路515号
515, Shen Fu Rd., Xin Zhuang Industrial Develop Zone, Shanghai, 201108, China
TEL:+86-21-3116-7799 FAX:+86-21-3462-7797
sales@ieiworld.com.cn www.ieiworld.com.cn