RM645

KEY FEATURES



Multiple Expansion

Supports 7 expansion slots

Rackmount Chassis

4U Short-Depth 19" Rackmount Standard



Optional support for redundant PSU request

Eazy maintainance with front acess design With front MB I/O interface

PANEL



motherboard I/O ports



Front View

Rear View



DIMENSIONS



SPECIFICATION

| DRIVE BAY | External/Internal | up to 8 x 2.5" drive bays |
|---------------------------------|------------------------|---|
| EXPANSION | Interface | 7 x Expansion Slot |
| RESERVED I/O HOLES (OPT.) | Front | N/A |
| | Rear | N/A |
| PANEL CONTROL/LED | Buttons | 1 x Power Switch |
| | | 1 x Power LED |
| | | 1 x HDD LED |
| COOLING | Fan | 2 x 120mm System Fan |
| POWER | Supply | PS/2-ATX |
| | | Mini-Redundant/1+1 Redundant PSU |
| PHYSICAL CHARACTERISTICS | Dimensions (W x H x D) | 481.5 x 175.6 x 470.8mm |
| | Weight | TBD |
| STANDARDS AND CERTIFICATIONS | Shock | Operating: 3G |
| | | Non-operating: 5G |
| | Vibration | Operating: random 5~500Hz 1G |
| | | Non-operating: Sweep Sine 10~500Hz 1.5G |

Front View