

W21

2U Active Air Cooler

PRODUCT SPECIFICATIONS

Speficiation Version: 12/31/2024

(Specifications are subject to change without notice)

W21 | LGA 5964**Model Number: W21**

- Recommend for LGA 5964 Processor
- Active Air Cooler for 2U Server and Up


Overall Specification

Dimension	144.1 x 93.0 x 70.6 mm
Weight	744g $\pm$ 10g
Material	Aluminum + Copper Heatsink Base + Heatpipe + Aluminum Fins
Thermal Interface Material	Shin-Etsu X23-8079-2 (or equivalent) Pre-Printed Tflex HD7.5 (or equivalent) Pre-Applied
TDP	Fully Support 400W at 41°C Ambient Temperature

Cooling Fan Specification


Model Number	DF126025BU - PWMH
Dimension	60 x 60 x 25 mm
Bearing	Double Ball
Rated Voltage	12V
Rated Speed	At Duty Cycle 0~20%: 2300 $\pm$ 10% RPM At Duty Cycle 50%: 5400 $\pm$ 10% RPM At Duty Cycle 100%: 11000 $\pm$ 10% RPM
Input Power	At Duty Cycle 0~20%: 0.84 W At Duty Cycle 50%: 2.76 W At Duty Cycle 100%: 18.0 W
Maximum Airflow	At Duty Cycle 0~20%: 11.91 CFM At Duty Cycle 50%: 28.38 CFM At Duty Cycle 100%: 58.31 CFM
Rated Static Pressure	At Duty Cycle 0~20%: 1.48 mm-H ₂ O At Duty Cycle 50%: 7.54 mm-H ₂ O At Duty Cycle 100%: 28.8 mm-H ₂ O
Acoustical Noise	At Duty Cycle 0~20%: 25.8 dBA At Duty Cycle 50%: 44.4 dBA At Duty Cycle 100%: 59.8 dBA
Lead Wire Pin Out	Pin#1- Black(-) Pin#2- Yellow(+) Pin#3- Green(Tachometer/ Signal Output) Pin#4- Blue (PWM)

W21 | LGA 5964



Performance Chart: W21 Thermal Resistance



Thermal Resistance vs. Fan Speed



CONFIDENTIAL DOCUMENT

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. MAY OTHERWISE AGREE TO IN WRITING.

REV#	DESCRIPTION	CHECKER	DATE
0.0	INITIAL RELEASE	MichaelF	11/11/24




11	HEATSINK SCREW CLIP	STEEL	4
10	THERMAL PAD SET	TFLEX HD7.5 OR EQUIVALENT	1
9	THERMAL GREASE	SHIN-ETSU X-23-8079-2 OR EQUIVALENT	N/A
8	FAN, LE06250019 (6025-11000RPM)	PBT	1
7	FAN BRACKET	SPCC	1
6	FAN BRACKET MOUNTING SCREW	STEEL	4
5	FAN SCREW	STEEL	4
4	HEATSINK	HEAT PIPES, AL6063 BASE, CU100 BASE BLOCK, AL1100 FIN	1
3	HEATSINK SPRING	SWC	4
2	WASHER	STEEL	4
1	HEATSINK SCREW	STEEL	4
ITEM #	DESCRIPTION	MATERIAL	QTY.

		DATE	NAME	 DYNATRON CORPORATION
DRAWN		11/11/24	MichaelF	
CHECKED		11/11/24	MichaelF	
ENG. APPR.				
MFG. APPR.				
QA				TITLE: 2U Active Air Cooler W21 BOM & Exploded Assembly Drawing
COMMENTS				
DWG. No: DYN-EP-W21				REV 0.0

NOTES:

1. THE FIGURE IS FOR REFERENCE ONLY, AND NOT FOR SCALE



Publication History:

12/31/2024: Thermal resistance vs. Fan Speed Release

11/11/2024: Initial Release

(Specifications are subject to change without notice)