



L44

2U Liquid Cooler

PRODUCT SPECIFICATIONS


Speficiation Version: 02/22/2024

(Specifications are subject to change without notice)

Model Number: L44


- Recommend for LGA 4926 Processor
- Liquid Cooler for 2U Server and Up
- Shin-Etsu X23-8079-2 Pre-Printed
- Fully Support 250W at 43°C Ambient Temperature

Cooling Fan Specification

Model Number	DF128038BX-E
Dimension	80 x 80 x 38 mm
Bearing	Double Ball
Rated Voltage	DC 12V
Rated Speed	At Duty Cycle 0~20%: 2400± 200 RPM At Duty Cycle 50%: 4800± 10% RPM At Duty Cycle 100%: 8000±10% RPM
Input Power	At Duty Cycle 0~20%: 1.2 W At Duty Cycle 50%: 5.52 W At Duty Cycle 100%: 24.72 W
Maximum Airflow	At Duty Cycle 0~20%: 32.52 CFM At Duty Cycle 50%: 67.24 CFM At Duty Cycle 100%: 115.61 CFM
Rated Static Pressure	At Duty Cycle 0~20%: 3.45 mm-H ₂ O At Duty Cycle 50%: 13.6 mm-H ₂ O At Duty Cycle 100%: 38.3 mm-H ₂ O
Acoustical Noise	At Duty Cycle 0~20%: 25.63 dBA At Duty Cycle 50%: 47.85 dBA At Duty Cycle 100%: 64.40 dBA
Lead Wire Pin Out	Pin#1- Black(-) Pin#2- Yellow(+) Pin#3- Green(Tachometer/ Signal Output) Pin#4- Blue (PWM) 

Performance Chart: Passive Cooler L44 Thermal Resistance



Thermal Resistance vs. Fan Speed



CONFIDENTIAL DOCUMENT

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD.
ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS DYNATRON
CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. MAY OTHERWISE AGREE TO IN WRITING.


REV#	DESCRIPTION	CHECKER	DATE
0.0	INITIAL RELEASE	Engr.	02/22/24



8	RADIATOR HOSE (HOT SIDE)	RUBBER	1
7	THERMAL GREASE	SHIN ETSU X23-8079-2	N/A
6	CP65 (WITH 90° BARB)	COPPER + PLASTIC	1
5	DY-RT_4926_SET	STEEL	1
4	RADIATOR HOSE (COLD SIDE)	RUBBER	1
3	RADIATOR (WITH PUMP60)	ALUMINUM ALLOY + PLASTIC	1
2	FAN, DF128038BX-E, 8000RPM	PLASTIC	3
1	FAN MOUNTING SCREW	STEEL	12
ITEM #	DESCRIPTION	MATERIAL	QTY.

DATE		NAME	 DYNATRON CORPORATION
DRAWN		02/22/24	
CHECKED		02/22/24	
ENG. APPR.			
MFG. APPR.			
Q.A.			TITLE: 2U Liquid Cooler L44 BOM & Exploded Assembly Drawing
COMMENTS:			
DWG. No: DYN-EP-L44			REV 0.0

NOTES:
1. THE FIGURE IS FOR REFERENCE ONLY, AND NOT FOR SCALE



DYNATRON CORPORATION

TITLE:

L44 Radiator
Overall Dimension Drawing

CONFIDENTIAL DOCUMENT

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. MAY OTHERWISE AGREE TO IN WRITING.

VIEW



UNITS

MM

DWG. No:

DYN-DM-2U_Radiator_L44



REV.

0.0

CONFIDENTIAL DOCUMENT

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO DYNATRON CORPORATION AND DYNACON INDUSTRIAL CO., LTD.
ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS DYNATRON
CORPORATION AND DYNACON INDUSTRIAL CO., LTD. MAY OTHERWISE AGREE TO IN WRITING.


REV#	DESCRIPTION	CHECKER	DATE
0.0	INITIAL RELEASE	Engr.	02/22/24



NOTES:

1. THE FIGURE IS FOR REFERENCE ONLY, AND NOT FOR SCALE

4	C-CLIP	STEEL	4
3	CP65 MOUNTING BRACKET (LGA4926)	STEEL	1
2	MOUNTING SPRING	STEEL	4
1	MOUNTING SCREW	STEEL	4
ITEM #	DESCRIPTION	MATERIAL	QTY.
DATE 02/22/24 NAME Engr. TOP MOTOR DYNATRON CORPORATION TITLE: CP65 Mounting Bracket Set DY-RT_4926_Set BOM & Exploded Assembly Drawing			
DWG. No:			REV
DYN-EP-DY-RT_4926_Set			0.0



Publication History:

02/22/2024: Initial Release

(Specifications are subject to change without notice)