

# FSP800-2Q01A

## FEATURES



- 800W CRPS Redundant Power Module
- Full range AC input, Active PFC
- 80+ Platinum Efficiency
- Working temperature up to 55°C (24 hours working)
- PMBus 1.2 Interface for digital power management
- Full protection functions (OVP, UVP, OCP, OTP, SCP.....)
- Hot-swap module without system shut-down
- Active current sharing function
- Best for Datacenter, storage and AI servers

## SAFETY STANDARD APPROVAL



## DESCRIPTION

FSP800-2Q01A is a redundant power supply module based on CRPS 2.0 standard. This power supply offers the total capacity up to 800 Watts, and uses a unique active PFC (Power Factor Correction) circuit design with high-load electrical components, which makes it perfect for use in industrial environments. It also features with PMBus interface, which makes PSU possible to communicate with motherboard for digital power management. In addition, this power supply is ideally the best choice for datacenter, workstation, AI & Edge, industrial automation applications.

## GENERAL SPECIFICATIONS

Dimension (L x W x H):	185 x 40.5 x 73.5 (mm)	Environment	
Efficiency:	94% @ 50% load & 230Vac	Working temperature:	0°C to 55°C (Full Loading)
Power factor:	0.98 @50% load, 230Vac 50Hz	Storage temperature:	-40°C to + 70°C
		Working humidity:	95% RH non-condensing
		Storage humidity:	95% RH non-condensing
Hold-up time at 100% loading:	115V / 60Hz: ≥ 12ms 230V / 50Hz: ≥ 12ms	MTBF (SR-332 Issue 2):	250,000 hours of continuous operation at 35°C, 100% output load
Input Inrush Current:	35A	Applications:	Datacenter, Storage, AI/Edge, IPC Controller

## INPUT SPECIFICATIONS

Input voltage:	90-264Vac/180-310Vdc
Input frequency:	47-63Hz
Input current:	8A @ 90Vac, 100% load

## OUTPUT RATING

Model	Output voltage (V)	Output current (A)
FSP800-2Q01A	12.2V	0 - 65 A
	12.2Vsb	0 - 2.1 A

## MECHANICAL SPECIFICATIONS

UNIT: mm

