


## EGPL-G2P1

### M.2 2280 to Dual PoE Module



#### HIGHLIGHT FEATURES

- Intel i210 controller
- Two independent PSE channels
- Complies with IEEE 802.3af, up to 15.4W at 48V per PoE port
- Complies with EN61000-4-2 (ESD) Air-15kV, Contact-8kV
- Supports 12V to 24V power input via 4-pin header
- Optional terminal mounting hole or bracket for daughter board
- Optional for 4-pin header or DC Jack power input
- Optional industrial temperature (-40°C to 85°C) support


#### SPECIFICATIONS

|                          |                                                                                                                                                      |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model Name               | EGPL-G2P1                                                                                                                                            |
| Module Type              | M.2 2280 to Dual PoE Module                                                                                                                          |
| Form Factor              | M.2 2280 B+M Key                                                                                                                                     |
| Function                 | PoE                                                                                                                                                  |
| Input I/F                | PCI Express 2.1 x1                                                                                                                                   |
| Output I/F               | PoE                                                                                                                                                  |
| Output Port              | 2                                                                                                                                                    |
| Output Connector         | RJ45                                                                                                                                                 |
| Max. Power Consumption   | 30W                                                                                                                                                  |
| Dimension (W x L x H/mm) | Main Board : 22 x 80 x 9.3<br>Daughter Board : 58.2 x 72.7 x 23.8                                                                                    |
| Temperature              | Operation : S/T 0° ~ 70°C ; W/T -40°C ~ 85°C (Ta)<br>Storage : -55°C ~ 95°C (Ta)                                                                     |
| Vibration                | 5G@[7~2000Hz]                                                                                                                                        |
| Shock                    | 50G@0.5ms                                                                                                                                            |
| OS Support               | Windows : XP (32bit), 7 (32 / 64bit), 8 / 8.1 (32 / 64 bit), 10 (32 / 64bit), and above version<br>Linux : Kernel 2.4 series, 2.6.x, and 3.x version |
| Warranty                 | 3 Years                                                                                                                                              |
| Notes                    | <ul style="list-style-type: none"><li>• Please download driver from Intel official website.</li></ul>                                                |


| P/N          | Description                                                                     |
|--------------|---------------------------------------------------------------------------------|
| EGPL-G2P1-C5 | M.2 2280 to Dual PoE Module, Mounting Hole, 4-pin Header / Standard Temperature |
| EGPL-G2P1-W5 | M.2 2280 to Dual PoE Module, Mounting Hole, 4-pin Header / Wide Temperature     |
| EGPL-G2P1-C6 | M.2 2280 to Dual PoE Module, Bracket, 4-pin Header / Standard Temperature       |
| EGPL-G2P1-W6 | M.2 2280 to Dual PoE Module, Bracket, 4-pin Header / Wide Temperature           |
| EGPL-G2P1-C7 | M.2 2280 to Dual PoE Module, Mounting Hole, DC Jack / Standard Temperature      |
| EGPL-G2P1-W7 | M.2 2280 to Dual PoE Module, Mounting Hole, DC Jack / Wide Temperature          |
| EGPL-G2P1-C8 | M.2 2280 to Dual PoE Module, Bracket, DC Jack / Standard Temperature            |
| EGPL-G2P1-W8 | M.2 2280 to Dual PoE Module, Bracket, DC Jack / Wide Temperature                |

# MECHANICAL DRAWING

# Main Board






# EGPL-G2P1-C5 / W5 Daughter Board and Mechanical Drawing




MECHANICAL DRAWING

EGPL-G2P1-C6 / W6 Daughter Board and Mechanical Drawing



Bracket




PIN DEFINE




| CAN Connector Pin Define |          |
|--------------------------|----------|
| 1                        | NC       |
| 2                        | GND      |
| 3                        | GND      |
| 4                        | 12 ~ 24V |

MECHANICAL DRAWING

Main Board







EGPL-G2P1-C7 / W7 Daughter Board and Mechanical Drawing







# MECHANICAL DRAWING

## EGPL-G2P1-C8 / W8 Daughter Board and Mechanical Drawing



## Bracket



HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales\_cn@innodisk.com

US T +1-510-770-9421 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp\_sales@innodisk.com

innodisk