



M.2 (P30) 4TE3

HIGHLIGHT FEATURES


- PCIe Gen 4 x4, NVMe 1.4
- Stable sustained performance
- LDPC ECC engine supported
- 256-bit AES hardware based encryption
- Hybrid write mode with SLC cache enable
- Dynamic thermal management

SPECIFICATIONS


Model Name	M.2 (P30) 4TE3
Flash Type	3D TLC
Interface	PCIe Gen 4 x4
Form Factor	M.2 2230 M Key
Capacity	128GB ~ 1TB
Sequential R / W (MB/sec, max.)	1,800 / 1,500
P/E Cycle	3,000
TBW (Max.)	932
Storage Temperature	-40°C ~ 85°C
Max. Power Consumption	3.1W
Max. Channels	4
External DRAM Buffer	N
H/W Write Protect	N
S.M.A.R.T.	Y
AES	Y (Optional)
TCG Opal	Y (Optional)
Dimension (W x L x H/mm)	Pure M.2 : 22.0 x 30.0 x 3.5 W/T with heat sink : 25.0 x 30.0 x 15.0
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	3 Years

DIAGRAM

ST



WT



Note: The appearance of silicone oil seeping out from the inside of the thermal pad is a normal occurrence. Silicone oil is not electrically conductive, so it does not impact the functionality of SSD.

ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
128GB	DEM23-A28DH1KCBDF	DEM23-A28DH1KWBDHFH
256GB	DEM23-B56DH1KCBDF	DEM23-B56DH1KWBDHFH
512GB	DEM23-C12DH1KCBDF	DEM23-C12DH1KWBDHFH
1TB	DEM23-01TDH1KCBDF	DEM23-01TDH1KWBDHFH

For TCG Opal function, the PN Code 10th ~ 12th will be DH2.

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales_cn@innodisk.com

US T +1-510-770-9301 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp_sales@innodisk.com

innodisk