

M.2 (S80) 3TS9-P

HIGHLIGHT FEATURES




- SATA III solution for industrial field
- High IOPS
- Excellent random performance
- End to end data path protection
- iData Guard for abnormal power failure
- Compatible with M.2 2280-D5-B-M standard

SPECIFICATIONS

Model Name	M.2 (S80) 3TS9-P
Flash Type	3D TLC
Interface	SATA III 6.0 Gb/s
Form Factor	M.2 2280 B+M key
Capacity	240GB ~ 480GB
Sequential R / W (MB/sec, max.)	540 / 340
P/E Cycle	3,000
TBW (Max.)	886
Storage Temperature	-40°C ~ 85°C
Max. Power Consumption	2.4W
Max. Channels	4
External DRAM Buffer	Y
H/W Write Protect	N
S.M.A.R.T.	Y
AES	N
TCG Opal	N
Dimension (W x L x H/mm)	22.0 X 80.0 X 4.25
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	5 Years

DIAGRAM



ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)
240GB	DSM28-240DT1NCAQFP
480GB	DSM28-480DT1NCAQFP

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales_cn@innodisk.com

US T +1-510-770-9421 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp_sales@innodisk.com

