

QBiX-Pro-AMLA7433REH-A1

Industrial system with Intel® Atom x7433RE/ Fanless Design/ Single Channel DDR5 up to 16GB/ 2 x HDMI



Features

- System Size : 178W x 125D x 52.7H (mm)
- Intel® Atom™ x7433RE Processor
- Single Channel DDR5, 1 x SO-DIMM
- 1 x COM Port (RS-232/422/485 & RI/5V/12V)
- 1 x COM Port (RS-232/422/485)
- 1 x Remote control
- 2 x 2.5GbE LAN Ports


Specifications

Dimension	System Size : 178W x 125D x 52.7H (mm)
CPU	Intel® Atom™ x7433RE Processor Intel 7, 4 cores, up to 3.40 GHz
Memory	1 x DDR5 SO-DIMM sockets, Max. Capacity 16 GB Support Single channel DDR5 4800 MHz memory modules
Ethernet	2 x 2.5GbE LAN Ports (Intel® I225V)
Graphic support	Integrated Graphics Processor - Intel® UHD Graphics support: 2 x HDMI 2.0 port, supporting a maximum resolution of 4096x2160 @60Hz (2 independent display outputs)
Audio	Realtek® ALC897
Storage	1 x 2.5" HDD/SSD (SATA 6Gb/s)
Expansion Slots	1 x 2280 M.2 M-Key (PCIe Gen3x2) 1 x 2230 M.2 E-Key 1 x Full-size mini PCIe with SIM slot
Front I/O	2 x RJ45 LAN Ports 2 x USB 3.2 Gen 2x1 2 x USB 2.0 2 x HDMI 1 x Power button with LED 1 x HDD LED 1 x Headphone Jack
Rear I/O	2 x USB 2.0 1 x COM Port (RS-232/422/485 & RI/5V/12V) 1 x COM Port (RS-232/422/485) 1 x GPIO (8 bits) 1 x Remote control 1 x 3-pin Terminal Block
Side I/O	2 x External Antenna Holes (Optional)
TPM	Onboard TPM 2.0 security chip INFINEON SLB9670VQ2.0
Power	+12V~36VDC (Full Range)
Operation temperature	Operating temperature: -20°C to 70°C Operating humidity: 40°C @ 20-95% (non-condensing) Non-operating temperature: -40°C to 85°C Non-operating humidity: 60°C @ 95% (non-condensing) Use wide temperature range memory and storage
Vibration During Operation	Operation: IEC 60068-2-64, 3 Grms, random, 5 ~ 500 Hz, 1 hr / Per Axis, With SSD/M.2 2280 Non-operation: IEC 60068-2-6, 2 G, Sine, 10 ~ 500 Hz, 1 Oct/min, 1 hr / Per Axis
Shock During Operation	Operation: IEC 60068-2-27, 50 G, half sine, 11 ms duration, With SSD
Mounting	Wall mount P/N: 25HB2-CGAA20-CHR x 1 (Optional) VESA 75/100 P/N: 25HB1-TPL021-S8R x 1 + 25KSD-000002-COR x 1 (Screw) (Optional)

GIGAIPC reserves the right to modify or change technical data without prior notice.

Dimension

Unit: mm



Packing Content

- Carton size: 505 x 333 x 231 (mm)
- Packing Capacity: 5pcs
- Single Box size: 313 x 191 x 95 (mm)
- Including:
 - Screw I Head For 2.5" HDD M3x8L x 4 (P/N: 25KSG-130081-K1R)
 - SATA Cable x 1 (P/N: 25CRI-150001-S9R)
 - 3-pin Terminal Blocks Male Plug x 1 (P/N: 25IO0-5ESDV0-D2R)
 - 2-pin Terminal Blocks Male Plug x 1 (P/N: 25IO0-EC3812-D2R)

Order Information

- System: 6BQP7433AMR-SI (Box packing)

2025/06/17

GIGAIPC reserves the right to modify or change technical data without prior notice.