

J20

1U Passive Air Cooler

PRODUCT SPECIFICATIONS

0| Socket


Model Number: J20

- Recommend FOR AMD® Socket SP7
- Passive Cooler for 1U Application

Overall Specification


Dimension	120 x 103.6 x 31.1mm
Weight	746g
Material	Copper Base & Copper Fins with Vapor Chamber
Thermal Grease	SHIN-ETSU 8195
TDP-AMD	


Lead Wire Pin Out Diagram :



Performance Chart: Passive Cooler J20 Thermal Resistance

Passive Cooler J20 Cooling Performance vs. Flow CFM







2

1

CONFIDENTIAL DOCUMENT

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DRAWING IS EXPRESSLY PROHIBITED EXCEPT AS DYNATRON CORPORATION AND DYNAEON INDUSTRIAL CO., LTD. MAY OTHERWISE AGREE TO IN WRITING.

REV#	DESCRIPTION	CHECKER	DATE
0.0	INITIAL RELEASE	MichaelZ	04/07/25



9	Thermal Grease	SHIN-ETSU 8195	1
8	C-Clip	STEEL	6
7	Heatsink	Copper Fins + VC	1
6	M3.5 Washer	STEEL	4
5	M4 Washer	STEEL	2
4	M3.5 Spring	STEEL	4
3	M3.5 Screw	STEEL	4
2	M4 Spring	STEEL	2
1	M4 Screw	STEEL	2
ITEM #	DESCRIPTION	MATERIAL	QTY.


	DATE	NAME	 DYNATRON CORPORATION	
DRAWN	4/7/2025	MichaelZ	TITLE: 1U Passive Air Cooler J20 BOM & exploded Assembly Drawing	
CHECKED	4/7/2025	MichaelZ		
ENG.APPR.				
MFG.APPR.				
COMMENTS:			DWG. NO. DYN-EP-J20	REV 0.0

NOTES:
THE FIGURE IS FOR REFERENCE ONLY, AND NOT FOR SCALE

2

1

Recommended Torque Application Pattern for Socket SP7 Coolers



WARNING: Failure to attach thermal solutions one-at-a-time in the sequence 1-2-3-4-5-6 and failure to remove thermal solutions one at a time in the sequence 6-5-4-3-2-1 can lead to permanent socket damage.

J20 | Socket SP7

Document History:

04/07/2025: Initial release