


ATX-PS2
HP2-6500P
Dimension :
140(D)*150(W)*86(H)/mm
FEATURES

- *Support - AC cable pull back from rear side(Optional)
- *Smart Fan Speed Control
- *Standard Dimension -ATX/PS2
- *Protections : OVP/OCP/SCP/OPP
- *Operation Altitude : 5000meters

INPUT CHARACTERISTICS

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
Operating Voltage Range		103		264	Vac
Input Frequency Range		47		63	Hz
Maximum Input Current	*Io=100% ; Low Line *Io=100% ; High Line			8 4	A
Leakage Current				3.5	mA
Inrush Current	*Vin=110Vac,Cold start/25°C *Vin=220Vac,Cold start/25°C			65 125	A

OUTPUT CHARACTERISTICS

WATTAGE	OUTPUT				
	5V	3.3V	12V	-12V	5VSB
500W	40A	30A	32A	1A	2A
Load Regulation	+/-5%	+/-5%	+/-5%	+/-5%	+/-5%
Ripple & Noise(mv)	60	60	100	100	60

*+5V and +3.3V total output max : 50A

ENVIRONMENTAL SPEC.

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
Temperature		0		50	°C
Relative Humidity	Non-condensing	20		80	%
Emissions	EN55032 FCC Part15	CLASS B			
Surge	EN61000-4-5	DM : +/-1KV CM : +/-2KV			
Harmonic Currents	EN 61000-3-2	CLASS D			

GENERAL SPEC.

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
MTBF	Io=100% ; Ta=25°C per MIL-HDBK-217F	180575			Hours
Efficiency	Io=100% ; Vin=115Vac		70		%
Power Density		4.53			W/in ³

