


2U Single
P2G-6510P
Dimension :
240(D)*100(W)*70(H)/mm

FEATURES

*Fan Reverse Option

*Protections : OVP/SCP/OCP/OPP

ENVIRONMENTAL SPEC.

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
Temperature		0		40	°C
Relative Humidity	Non-condensing	20		80	%
Emissions	EN55032 FCC Part15	CLASS B			
Surge	EN61000-4-5	DM : +/-1KV CM : +/-2KV			
Harmonic Currents	EN 61000-3-2	CLASS D			

GENERAL SPEC.

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
MTBF	Io=100% ; Ta=25°C per MIL-HDBK-217F	172642			Hours
Efficiency	Io=100% ; Vin=115Vac		71		%
Power Density		4.97			W/in ³

INPUT CHARACTERISTICS

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
Operating Voltage Range		103		264	Vac
Input Frequency Range		47		63	Hz
Maximum Input Current	*Io=100% ; Low Line *Io=100% ; High Line			8 4	A
Leakage Current				3.5	mA
Inrush Current	*Vin=110Vac,Cold start/25°C *Vin=220Vac,Cold start/25°C			55 110	A

OUTPUT CHARACTERISTICS

WATTAGE	OUTPUT					
	5V	3.3V	12V	-12V	-5V	5VSB
510W	33A	28A	32A	1A	0.8A	2A
Load Regulation	+/-5%	+/-5%	+/-5%	+/-5%	+/-5%	+/-5%
Ripple & Noise(mv)	60	50	100	150	120	60

*+5V and +3.3V total output max : 45A

