


2U Single
P2G-5600V
Dimension :
240(D)*100(W)*70(H)/mm
FEATURES

- *80 PLUS BRONZE
- *Fan Reverse Option
- *Protections : OVP/SCP/OCP/OPP
- *Operation Altitude : 5000meters

INPUT CHARACTERISTICS

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
Operating Voltage Range		90		264	Vac
Input Frequency Range		47		63	Hz
Maximum Input Current	*Io=100% ; Low Line			9	A
	*Io=100% ; High Line			4	
Leakage Current				3.5	mA
Inrush Current	*Vin=115Vac,Cold start/25°C			25	A
	*Vin=230Vac,Cold start/25°C			50	

OUTPUT CHARACTERISTICS

WATTAGE	OUTPUT				
	5V	3.3V	12V	-12V	5VSB
600W	25A	25A	46A	0.8A	3.5A
Load Regulation	+/-5%	+/-5%	+/-5%	+/-5%	+/-5%
Ripple & Noise(mv)	60	60	120	120	60

*+5V and +3.3V total output max : 160W

ENVIRONMENTAL SPEC.

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
Temperature		0		50	°C
Relative Humidity	Non-condensing	20		80	%
Emissions	EN55032 FCC Part15	CLASS B			
Surge	EN61000-4-5	DM : +/-1KV CM : +/-2KV			
Harmonic Currents	EN 61000-3-2	CLASS D			

GENERAL SPEC.

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
MTBF	Io=100% ; Ta=25°C per MIL-HDBK-217F	98144			Hours
Efficiency	Io=100% ; Vin=115Vac		80		%
Power Density		5.85			W/in ³

