

Preliminary




Features

- 55" active screen size
- IPS Display Technology
- UHD Resolution (3840x2160)
- 500nits High Brightness
- 24 x 7 operation
- 50,000 hours LED life
- Optimized for Video Wall (2 x 2 Matrix)
- 4-Size Even Narrow Border (10.8mm) to meet Video Wall uses
- Support Landscape & Portrait
- IP5X rating: Dust-Protected

Specifications

| Brand | | | Advantech |
|--------------------------|------------------------------|----------------------------------|-----------------------------|
| Display | Active Screen Size | 55 inch | |
| | Panel Type | IPS | |
| | Resolution | 3840 x 2160 (UHD) | |
| | Brightness | 500 nits (Typ.) | |
| | Operation (Hours/Day a week) | 24/7 | |
| | Contrast Ratio | 1200:1 (Typ.) | |
| | Aspect Ratio | 16:9 (Wide) | |
| | Viewing Angle | 89° / 89° / 89° / 89° (Typ.) | |
| | Response Time | 8 ms | |
| | Backlight Life (hours) | 50,000 (Typ.) | |
| Touch | Touch Type | N/A | |
| | Touch Function | N/A | |
| | Touch Interface | N/A | |
| | Touch Method | N/A | |
| | Stylus Pen | N/A | |
| Connectivity | Input | Video | HDMI2.0 x 3 |
| | | Audio | Audio line in x 1 |
| | | Control | N/A |
| | Output | Other slots/ports | USB A 2.0 x 2 |
| | | Video | N/A |
| | | Audio | 10W+10W Internal Speaker |
| | | Control | IR Remote Control, RS232 |
| System | OS | N/A | |
| | CPU | N/A | |
| | Memory | N/A | |
| | OSD Language | TBD | |
| | OSD Function | TBD | |
| Power | Power Type | Internal power board | |
| | Power Input-AC | 110-240V _{AC} , 50-60Hz | |
| | Power Consumption | 135W (Typ.) | |
| Environment | Operating | Temperature | 0°C ~ 40°C |
| | | Humidity | 10% to 85% (non-condensing) |
| | Storage | Temperature | -20 ~ 60 °C |
| | | Humidity | 10% to 80% (non-condensing) |
| Mechanical Specification | Housing Material | | Texture (Black) |
| | Waterproof Rating | | N/A |
| | VESA Compatibility | | 400 x 200 (M6) |
| | Side mount screw hole | | N/A |
| | Hand Holder/Stand | | N/A |
| | Cable Management | | N/A |
| | Dimensions (W x H x D) | Physical without stand | 1234.2*706.5*58.9 mm |
| | | Packing | 1380*825*118 mm |
| | Weight | Net | 12.0 kg |
| | | Gross | 15.4 kg |
| Installation | Installation rotation | | Portrait & Landscape |
| | Mounting on a wall | | VESA Mount: 400 x 200 (M6) |
| | Mounting with stand/arm | | TBD |
| | Mounting through bracket | | N/A |
| | Extending PC/peripherals | | N/A |
| Certificate | | BSMI, CB, CCC, CE, FCC | |
| Warranty | | 2-year (1-year for panel) | |



| DIMENSION (UNIT: mm) | |
|----------------------------------|--------|
| A (SET Width) | 1234.2 |
| B (SET Height Without Stand) | 706.7 |
| E (Set Depth, Back cover) | 58.9 |
| F (Set Depth, Middle cover) | 40.4 |
| G (Set Depth, Front Frame) | 11.2 |
| I (Wall Mount, Horizontal) | 400 |
| J (Wall Mount, Vertical) | 200 |
| K (Active Area, Horizontal) | 1209.6 |
| L (Active Area, Vertical) | 680.4 |
| Wall Mount Screw | M6*15 |
| M(From Cabinet End to IR Sensor) | 255.2 |

| | Width(mm) | Height(mm) | Depth(mm) | Bezel Width (front) |
|------------------|-----------|------------|-----------|---------------------|
| None touch model | 1234.2 | 706.7 | 58.9 | 10.8 |

Ordering Information

| Part Number | Description | Packing List |
|--------------------|--|--|
| None touch model | | <ul style="list-style-type: none"> HDMI cable Remote control Power cable (Optional Accessory) |
| VWK-9550-UD50SX-B0 | Advantech 55" Ultra HD Digital Signage | |

Optional Accessory

| Part Number | Description |
|-------------|-------------|
| | |