

OFM-3700

37" High Brightness Stretched Display (CVD)



Product Features

- 37"1920x540 Resolution
- Hi Tni panel
- Sunlight readable
- IK10
- Application : Transportation
- High Brightness
- Optical Bonding with Low reflect cover glass
- IP65
- Wide Operating Temperature

Specification

Certification	
Certification Information	EN50155/EN45545
External I/O	
HDMI	1x HDMI
Panel	
LCD Size	37"
Resolution	1920 x 540
Luminance	1000 cd/m2
Contrast ratio	5000
Frame Rate (Hz)	60
Active Display Area (mm)	904.32 x 254.34
Response time	11 ms

Mechanical & Environmental

Operating Temp. -25°C ~ 55°C

Storage Temp. -30°C ~ 85°C

Power Consumption (W/max.) 85

Power Requirement +24~+110V DC In

Dimension (W x L x H) 961 x 290.9 x 86.76 mm

Ordering Information

Ordering Information

OFM-3700-X000G-1R
37" Open frame transportation monitor/ 1920 x 540/ 1000nits/ HDMI/ DC-IN/
EN45545/EN50155 certify/+24 ~ 110V DC-in

VMS-RPPS
Intel® 13th Core 7/5/3/Celeron® Processor/4LAN/4COM/4USB/2DP/2HDMI

VMS-CFS
8th/9th Gen Intel® Core™ i7/i5/i3/Pentium®/Celeron®
Processors/2LAN/3COM/4USB/1DP/2HDMI

AIB-Q6490
Qualcomm® Kryo™ 670, 8 cores, up to 2.7 GHz, 12 TOPS
(INT8)/1LAN/1COM/6USB/1HDMI/DC IN

AIB-3588
Rockchip RK3588/2LAN/4USB/1HDMI IN/2HDMI OUT/1Type C DP/DC IN

AIB-3566
Rockchip RK3566/1LAN/2USB/1HDMI IN/1HDMI OUT/DC IN