

PC PSU FSP400-60GHS(85)

DESCRIPTION

This is the specification of Model UFSP400-60GHS(85)U; AC-line powered switching power supply with active PFC (Power Factor Correction) circuit, meet EN61000-3-2 and with Full Range Input features. Also, +5Vsb power is less than 0.5Winput at power off mode (PS_ON input at high state) which is comply with ErP Lot 6 year 2013 requirement

APPLICATION

Desktop, Mini-itx

WATTAGE

400W Wattage:

DIMENSION

100mm(L) x 125mm(W) x Dimension:

63.5mm(H)

PRODUCT HIGHLIGHT

Efficiency Level: 80PLUS Bronze Erp Lot: <0.5W Input Voltage: 100~240Vac

INPUT SPECIFICATION

Input Range: 100-240 Vac Input Frequency: 47-63 Hz

Input Current: 115V@ <4.5 Amps-rms 230V@

< 2.5 Amps-rms

OUTPUT SPECIFICATION

+ 3.3Vdc : 20ms Maximum + 5 Vdc : 20ms Maximum **Output Rise Time:**

+ 12 Vdc : 20ms Maximum + 5 Vsb : 20ms Maximum - 12 Vdc: 20ms Maximum



SAFETY STANDARD APPAOVAL







GENERAL SPECIFICATION

Efficiency: 80PLUS Bronze
PWOK Delay Time: 500ms > PWOK > 100ms
EMC Performance: EN55022 class B
EN55024

EN 61000-3-2 EN 61000-3-3

ENVIRONMENTAL SPECIFICATION

TEMP.Range: Operating Temperature:10°C to

+50°C Storage Temperature: -20°C to +

80℃

The power supply reliability, when calculated by MIL-HDBK-217;latest MTBF:

revision, are exceed 100,000 hours with all output at Typical load and an

ambient temperature of 25℃.

*Output Voltage and Current Rating

o depart voltage and out telle realing						
	+3.3V	+5V	+12V1	+12V2	-12V	+5Vsb
Ripple-Noise(R-P) mV	70mV	70mV	140mV	140mV	140mV	70mV
Regulation Load %	±5%	±5%	±5%	±5%	±10%	±5%
Output Max.(A)	21A	22A	17A	16A	0.5A	2.5A
Output Min.(A)	0.1A	0.2A	0.1A	0.5A	0A	0A

- (1)+3.3V & 5V total output not exceed 120W
- (2)Total output continuous shall not exceed 400W watts.

This content is subject to change, please refer to specification for more detail. FSP reserve the right to change the content without prior notice