



Adapter FSP120-ABCN2

DESCRIPTION

19V/ 120 wats/ C6 AC inlet with 25.4 mm height

APPLICATION

IPC systems, Embedded systems, Printers, POS systems

FEATURES

- Meet Energy Star EPS2.0/ErP lot 7
- Meet DOE Level VI
- High Altitude 5,000M
- Semi Slim Size- Height 25.4 mm
- High Reliability
- EMC Standard: EN55022 CLASS B / EN55024 CLASS B
- Over Current Protection
- Over Temperature Protection
- Over Voltage Protection
- With PFC Circuit

WATTAGE

Wattage: 120W

PRODUCT HIGHLIGHT

V-Output: 19
O/P Current: 6.32
Socket Type: C8

INPUT ELECTRICAL

Input Voltage: 90 ~ 264 V
Input Frequency: 47 ~ 63 Hz

OUTPUT ELECTRICAL

Single Output: 19 V/ 6.31 A

SAFETY STANDARD APPAOVAL



NO LOAD AND EFFICIENCY

No Load: 0.21 Watts
Efficiency: ≥ 88 %

ENVIRONMENTAL REQUIREMENTS

Altitude : 5000 M

MECHANICAL

Dimension: 151.3mm(L) x 75.6mm(W) x 25.4mm(H)

LED Indicator: No
On/ Off Switch: No

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice