

# Hyper TX3 EVO (EU Version)

#### **Features**

- 3 direct contact heat pipes with a base that is engineered to minimize CPU contact gaps
  providing excellent heat conduction.
- Option for adding 2nd fan with quick-snap fan brackets to increase cooling performance.
- A mere 17 dBA (minimum speed) is accomplished by utilizing a silent 92mm PWM fan with a wide RPM range.
- Versatile all-in-one mounting solution supporting the latest Intel® LGA 1366 / 1155 and AMD FM1 / AM3+.
- Excellent airflow design with compact heat sink dimension.



RR-TX3E-22PK-R1

#### Compatibility

#### All Intel® Socket 1366/1156 1155/775 CPU

- Intel® Core™ i7 Extreme
- Intel® Core™ i7
- Intel® Core™ i5
- Intel® Core™ i3
- Intel® Core™2 Extreme/Quad/Duo
- Intel® Pentium®
- Intel® Celeron®

#### AII AMD Socket FM1/AM3+/AM3 AM2+ / AM2 CPU

- AMD FX-Series
- AMD A-Series
- AMD Phenom™ II X4 / X3 / X2
- AMD Phenom™ X4 / X3
- AMD Athlon™ II X4 / X3 / X2
- AMD Athlon™ X2
- AMD Athlon™
- AMD Sempron™

(For the latest CPU support information, please visit our website.)

#### **Specifications**

CPU Socket	Intel® Socket LGA1366/1156/1155/775
	AMD Socket FM1/AM3+/AM3/AM2+/AM2
Dimensions	90 x 79 x 136 mm (3.5 x 3.1 x 5.4 inch)
Heat Sink Dimensions	90 x 51 x 136 mm (3.5 x 2.0 x 5.4 inch)
Heat Sink Material	3 Direct Contact Heat Pipes / Aluminum Fins
Heat Sink Weight	306g (0.68 lb)
Fan Dimensions	92 x 92 x 25 mm (3.6 x 3.6 x 1 inch)
Fan Speed	800 - 2200 RPM (PWM) ± 10%
Fan Air Flow	15.7 - 43.1 CFM ± 10%
Fan Air Pressure	0.35 - 2.63 mmH <sub>2</sub> O ± 10%
Fan Life Expectancy	40,000 hours
Noise Level	17 - 30 dBA
Bearing Type	Long Life Sleeve Bearing
Connector	4-Pin
Fan Weight	73g (0.16 lb)
Weight	386g (0.85 lb)



# Hyper TX3 EVO (EU Version)



#### **3 Direct Contact Heat Pipes**

Aluminum fins with 3 direct contact heat pipes to provide excellent heat dissipation.



# **Improved Direct Contact Heat Pipe Base**

A base engineered to minimize CPU contact gaps with exceptional heat conduction ability.



#### **Compact Dimension**

Excellent airflow design with compact heat sink dimension.



#### **All-in-one Mounting Solution**

Compatible with Intel® Socket LGA 1366/1156/1155/775 and AMD Socket FM1/AM3+/AM3/A M2+/AM2.



### **Dual-Fan Design**

Supports an optional 2nd 92mm fan to increase cooling performance.



## 92mm PWM Fan with Quick-snap Fan Bracket Design

Includes a new 92mm PWM fan with anti-vibration rubber pads and a quick-snap cover for an easily expedited fan installation.



## Package Information

EAN Code: 4719512033487UPC Code: 884102013652

Package Dimensions: 149 x 104 x 210 mm

5.9 x 4.1 x 8.3 inch

Carton Dimensions: 540 x 310 x 239 mm
21.3 x 12.2 x 9.4 inch

10pcs per carton

48 cartons per pallet

